

M A T E R I A L S A F E T Y D A T A S H E E T

I. IDENTIFICATION

MANUFACTURED BY: Diamond Vogel Paint
1506 Bluff Road
Burlington, IA 52601-0247

REVISED: 06/28/2006
PRINTED: 07/05/2006

24 Hour Emergency Telephone
CHEMTREC 1-800-424-9300

General Information:
Mon-Fri 8 AM - 5 PM
712-737-4993

TRADE NAME: Low VOC Yellow Traffic L/F

MFG. PRODUCT NUMBER: TM-3783

II. HAZARDOUS INGREDIENTS

CAS #67-64-1	Acetone	WT %: 20-50	Footnote: (1)
ACGIH TLV: 500 ppm TWA	ACGIH STEL: 1000 ppm		
OSHA PEL: 1000 ppm TWA	OSHA CEILING:	OSHA PEAK:	
VAPOR PRESSURE: 185mm Hg60F	LEL%: 2.6%		
CAS #14808-60-7	Crystalline Silica	WT %: 1-5	Footnote: (2)
ACGIH TLV:	ACGIH STEL:		
OSHA PEL:	OSHA CEILING:	OSHA PEAK:	
VAPOR PRESSURE:	LEL%:		
CAS #117-81-7	Bis(2-ethylhexyl)phthalate (DEHP)	WT %: 0.997	
ACGIH TLV: 5 mg/m3 TWA	ACGIH STEL:		
OSHA PEL: 5 mg/ m3 TWA	OSHA CEILING:	OSHA PEAK:	
VAPOR PRESSURE: <.01 mm Hg	LEL%: 474F		
CAS #1330-20-7	Xylene	WT %: 1-5	Footnote: (1)
ACGIH TLV: 100 ppm TWA	ACGIH STEL: 150 ppm		
OSHA PEL: 100 ppm TWA	OSHA CEILING:	OSHA PEAK:	
VAPOR PRESSURE: 6.6mmHg@20C	LEL%: 1.0%		
CAS #100-41-4	Ethyl Benzene	WT %: 0.916	
ACGIH TLV: 100 ppm TWA	ACGIH STEL: 125 ppm		
OSHA PEL: 100 ppm TWA	OSHA CEILING:	OSHA PEAK:	
VAPOR PRESSURE:	LEL%:		

WARNING MESSAGES:

- (1) Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Chronic exposure may cause damage to the central nervous system, respiratory system, lung, eye, skin, liver, gastrointestinal tract, spleen, kidneys, and blood.
- (2) IARC Monograph Volume 68, 1997 concludes that there is sufficient evidence that inhaled crystalline silica causes cancer in humans. IARC group 1. The NTP, in the Sixth Annual Report on Carcinogens, 1991, has added crystalline silica to its list of substances that are anticipated to be carcinogens.
- (3) See Section IX for reportable Hazardous Air Pollutants.

III. PHYSICAL DATA

BOILING RANGE: 133-727° F

EVAPORATION RATE: * slower than ether *

PERCENT VOLATILE BY VOLUME: 50.70%

WEIGHT PER GALLON: 11.33 LBS

VAPOR DENSITY: * heavier than air *

ACTUAL VOC (lb/gal): 0.59

EPA VOC (lb/gal): 1.03

EPA VOC (g/L): 123.44

IV. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: -17° C 1° F

LEL: Refer to Section II

FLAMMABILITY CLASSIFICATION: CLASS 1B

HAZARD CLASSIFICATION: *Flammable Liquid

EXTINGUISHING MEDIA: *carbon dioxide, dry chemical, or fire foam*

UNUSUAL FIRE AND EXPLOSION HAZARDS: With excessive heat, cans will rupture from internal pressure and discharge flammable contents. Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build up of vapors by opening all windows and doors to achieve cross-ventilation.

SPECIAL FIREFIGHTING PROCEDURES: Burning will produce toxic fumes. Wear self-contained breathing apparatus and full turn-out gear to fight fires. USE WATER WITH CAUTION. Material will float and may ignite on surface of water. Use water spray to keep fire exposed containers cool. Water may be ineffective in fighting the fire.

V. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II.

EFFECTS OF OVEREXPOSURE:

Acute- High vapor concentrations are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. Product has a low order of acute oral and dermal toxicity, but minute amounts aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.

Chronic- Xylene contains ethylbenzene which has been classified as a possible carcinogen to humans, Group 2B, by the International Agency for Research on Cancer (IARC), based on sufficient evidence in laboratory animals but inadequate

evidence for cancer in humans. Prolonged or repeated overexposure to ethylbenzene may cause the following: kidney effects, liver effects, lung effects, thyroid effects, testicular effects.

NTP has classified Bis (2-ethylhexyl phthalate) as a Group 2 carcinogen. There is limited evidence of carcinogenicity in experimental animals.

This product contains crystalline silica which may cause delayed respiratory disease (silicosis) if inhaled over a prolonged period of time. Avoid breathing dust. Use a NIOSH/MSHA approved respirator where TLV for crystalline silica may be exceeded.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Eye disease, Skin disorders and Allergies

PRIMARY ROUTE(S) OF ENTRY: Eyes, Ingestion, Skin, Inhalation

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. Restore breathing. Treat symptomatically. Consult a physician.

EYES: Flush immediately with large amounts of water for at least 15 minutes. Talk to a physician for medical treatment.

SKIN: Wipe off with towel. Wash with soap and water. Remove contaminated clothing.

INGESTION: If swallowed, call a physician immediately. Remove stomach contents by gastric suction or induce vomiting only as directed by a medical personnel. Never give anything by mouth to an unconscious person.

VI. REACTIVITY DATA

STABILITY: *stable*

HAZARDOUS POLYMERIZATION: *will not occur*

INCOMPATIBILITY: oxidizing agents, halogens, strong reducing agents and strong bases.

HAZARDOUS DECOMPOSITION PRODUCTS: Fire, burning and welding may generate carbon monoxide.

CONDITIONS TO AVOID: Fire, burning, and welding.

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition (flames, hot surfaces and electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. Use non-sparking tools. Remove with inert absorbant.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and

federal regulations.

VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

If air concentrations above the TLV are possible, wear a NIOSH/MSHA approved respirator.

VENTILATION: Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV and LEL of most hazardous ingredient in Section II, below acceptable limit.

PROTECTIVE GLOVES: Permeation resistant gloves (butyl rubber, nitrile rubber) should be used. Cover as much of the exposed skin area as possible with appropriate clothing.

EYE PROTECTION:

Splash proof eye goggles. In emergency situations, use eye goggles with a full face shield.

OTHER PROTECTIVE EQUIPMENT: Protective clothing such as coveralls or lab coats must be worn.

HYGIENIC PRACTICES: See Section V

IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN DURING HANDLING AND STORAGE:

Keep away from heat. Keep away from sparks, flames and other sources of ignition. Store in a cool, dry place. Keep container closed when not in use. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use with adequate ventilation. Ground and bond containers when transferring material. Use explosion proof equipment. Follow all MSDS/label precautions even after the container is emptied because it may retain product residues. Wash thoroughly after handling.

OTHER PRECAUTIONS: * none *

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

Ingredient	CAS #	Wt% of HAPS in product	Pounds HAPS/ Gal product
-----	-----	-----	-----
Xylene	1330-20-7	4.3 %	0.5
