



SE-Series

Double Hide Field Marking Paint

Product Data Sheet

PRODUCT DESCRIPTION

Diamond Vogel's Double Hide Field Marking Paint is a acrylic vinyl latex concentrate designed for exterior marking.

TYPICAL USES

Double Hide Field Marking Paint is formulated to be used on football fields, tracks and courts. Suitable substrates that this coating may be applied to would be turfs, concrete, asphalt and cinders.

COLORS AVAILABLE

SE-1617 White
SE-3626 Yellow
SE-0634 Neutral Base 4-14 oz/gal

PHYSICAL PROPERTIES (SE-1617)

Resin Type Acrylic Vinyl Latex
Clean-up Solvent Water
Finish 0-5 @ 85°
Solids by Weight 55 %
Solids by Volume 34 %

Recommended Dry Film
Thickness per Coat 1.5 – 2 mils

Wet Film to Achieve DFT 4.5 – 6 mils

Theoretical Coverage
@ 1 mil 545 ft²/gallon

Practical Coverage at
Recommended DFT¹ 273 – 363 ft²/gallon

Dry Times²
@ 70° F (21° C)
and 50% R.H. Touch 30 minutes

VOC's 53 grams/liter
(ranges from 53 to 80 depending on color)

1 Spread rates are estimates based on products volume solids and make no allowance for material loss during application. Actual spread rates may vary dependent on applicator experience, surface porosity and texture.

2 Dry times may vary depending upon temperature, humidity and degree of air movement.

SPECIFICATIONS

Concrete
Self Priming

Turf
Self Priming

Asphalt
Self Priming

Cinders
Self Priming

For more detailed recommendations, please contact your local Diamond Vogel Sales Representative.

SURFACE PREPARATION

All surfaces should be dry and clear of debris. Cut grass to desired height. Properly prepare surfaces prior to applying.

Do not apply if rain or inclement weather is expected.

Concrete, Asphalt, Cinders, and Turf

- Concrete and asphalt surfaces should be power washed, or swept to remove all dirt and foreign materials, to promote good coating adhesion.

APPLICATION

- Equipment must be clean prior to start. Flush airless lines with clean water.
- This product is designed to be applied by line marking equipment but may also be applied by brush or roller. Select a roller cover suited for the texture of the surface to be coated.
- If thinning is desired, you may mix up to three parts of water to one part of concentrate. Proportions may be varied depending on the surface to be marked and the brightness desired.
- Be sure to mix thoroughly before and during application.
- The spread rate will depend on the ratio of paint concentrate to water, and the type of surface to which it is applied.

ENVIRONMENTAL VARIABLES

Protect from freezing prior to and during application. Minimum surface and air temperature required for application is 50° F (10° C) and at least 5° F (3° C) above the dew point. Curing is affected by temperature, humidity and air movement. The minimums must be maintained for at least eight hours in order to achieve proper film formation. Application at elevated temperatures, wind conditions, and/or low humidity require special application procedures to achieve proper film formation.

CLEAN-UP

Clean up spills immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment.

CAUTIONS

Do not apply below 50° F.

Protect from freezing

Do not take internally

Use with adequate ventilation

KEEP OUT OF REACH OF CHILDREN

*WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Diamond Vogel Paints does not control the application of its products, or the condition of the surfaces to which they are applied, Diamond Vogel Paint's liability will under no circumstances exceed replacement of the product.