

## M A T E R I A L   S A F E T Y   D A T A   S H E E T

## I. IDENTIFICATION

MANUFACTURED BY: Diamond Vogel Paint  
2100 North Second Street  
Minneapolis, MN 55414

REVISED: 09/15/2009  
PRINTED: 09/22/2009

24 Hour Emergency Telephone  
CHEMTREC 1-800-424-9300

General Information:  
Mon-Fri 8 AM - 5 PM  
712-737-4993

TRADE NAME: V-Tech 505 Concrete Epoxy Primer (Pt B)

MFG. PRODUCT NUMBER: LM-0209

## II. HAZARDOUS INGREDIENTS

Trade Secret		WT %:	20-50
ACGIH TLV: NE	ACGIH STEL: NE		
OSHA PEL: NE	OSHA CEILING: NE		OSHA PEAK: NE
VAPOR PRESSURE: NA	LEL%: NA		
CAS #1330-20-7	Xylene	WT %:	20-50
ACGIH TLV: 100 ppm	ACGIH STEL: 150 ppm		Footnote: (1)
OSHA PEL: 100 ppm	OSHA CEILING: NE		OSHA PEAK: NE
VAPOR PRESSURE: 7 mmHg@20C	LEL%: 1		
CAS #100-41-4	Ethyl Benzene	WT %:	5-20
ACGIH TLV: 100 ppm	ACGIH STEL: 125 ppm		Footnote: (2)
OSHA PEL: 100 ppm	OSHA CEILING: NE		OSHA PEAK: NE
VAPOR PRESSURE: 10 mmHg@20C	LEL%: 1		
CAS #108-65-6	PropyGlycolMethyleEtherAcet	WT %:	5-20
ACGIH TLV: NE	ACGIH STEL: NE		Footnote: (1)
OSHA PEL: NE	OSHA CEILING: NE		OSHA PEAK: NE
VAPOR PRESSURE: 3.7mmHg@20C	LEL%: 1.5		
Trade Secret		WT %:	1-5
ACGIH TLV: n.e.	ACGIH STEL: n.e.		
OSHA PEL: n.e.	OSHA CEILING: n.e.		OSHA PEAK: n.e.
VAPOR PRESSURE: 0.01 mmHg@21c	LEL%:		
CAS #25068-38-6	Bis A,Epichlorohydrin Epoxy	WT %:	1-5
ACGIH TLV: NE	ACGIH STEL: NE		
OSHA PEL: NE	OSHA CEILING: NE		OSHA PEAK: NE
VAPOR PRESSURE: .02mmHg@20C	LEL%: NA		

## WARNING MESSAGES:

- (1) Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Chronic exposure may cause damage to the central nervous system, respiratory system, lung, eye, skin, liver, gastrointestinal tract, spleen, kidneys, and blood.
- (2) International Agency for Research on Cancer (IARC) Monograph Volume 77 (2000) concluded that Ethylbenzene is "possibly carcinogenic to humans (Group 2B)" based on inadequate evidence in humans and sufficient evidence in experimental animals.
- (3) See Section IX for reportable Hazardous Air Pollutants.

## III. PHYSICAL DATA

BOILING RANGE: 266-295° F

EVAPORATION RATE: \* slower than ether \*

PERCENT VOLATILE BY VOLUME: 65.92%

WEIGHT PER GALLON: 7.59 LBS

VAPOR DENSITY: \* heavier than air \*

ACTUAL VOC (lb/gal): 4.82

EPA VOC (lb/gal): 4.82

EPA VOC (g/L): 577.63

#### IV. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 27° C 81° F

LEL: Refer to Section II

FLAMMABILITY CLASSIFICATION: CLASS 1C

HAZARD CLASSIFICATION: \*Flammable Liquid

EXTINGUISHING MEDIA: Use water spray, dry chemical, foam, or Carbon Dioxide. Use water spray to cool fire-exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARD: Keep away from heat, sparks, and flame. May generate toxic or irritating combustion products. May generate carbon monoxide or toxic nitrogen gases.

SPECIAL FIRE FIGHTING PROCEDURES:

In case of fire and/or explosion do not breathe fumes. Use water spray to reduce vapors. If water pollution occurs, notify appropriate authorities. Wear NIOSH approved self-contained breathing apparatus with independent air supply. Keep containers cool with water spray. Avoid skin contact.

#### V. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II.

EFFECTS OF OVEREXPOSURE:

ACUTE-

Eye Contact: Severe irritant, chemical burn possible, possible tissue damage. High vapor concentrations are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

Skin Contact: Severe irritant, corrosion to tissue, possible skin burns.

Inhalation: Moderate to severe irritant. Minute amounts aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly

death.

Ingestion: Severe irritation, possible gastrointestinal tract.

May causes nausea unless treated promptly.

CHRONIC- Caused burns to exposed tissue.

Xylene contains ethylbenzene which has been classified as a possible carcinogen to humans, Group 2B, by the International Agency for Research (IARC), based on sufficient evidence in laboratory animals but inadequate evidence for cancer in humans. Prolonged or repeated overexposure to ethylbenzene may cause the following: kidney effects, liver effects, lung effects, thyroid effects, testicular effects, pituitary effects.

Repeated contact can result in defattig and drying of the skin which may result in skin irritation and dermatitis.

Repeated contact with the skin may cause allergic reaction/sensitization. Prolonged inhalation may result in central nervous system depression which may be evidenced by giddiness, headache, dizziness and nausea; in extreme cases, unconsciousness and death may occur. Prolonged exposure to low concentrations of vapor may cause: sore throat, eye irritation, nausea, headache.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Asthma, Chronic respiratory disease (e.g. Bronchitis, Emphysema)

Eye disease, Skin disorders and Allergies.

PRIMARY ROUTE(S) OF ENTRY: Ingestion, Skin Absorption, Inhalation

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT- Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Call a Physician.

SKIN CONTACT- Remove product and immediately flush affected area with water for at least 15 minutes. Call a physician. Except in the most minor, superficial and localized burns, cover the affected area with a sterile dressing or clean sheeting and transport for medical care. DO NOT APPLY GREASES OR OINTMENTS. Control shock if present.

INHALATION- Move patient to fresh air. If breathing has stopped or is labored give mouth-to-mouth respiration. Supplemental oxygen may be indicated. Prevent aspiration of vomit. Turn victim's head to the side. Assure mucus does not obstruct airway. Call a physician.

INGESTION- In the event of ingestion, administer 3-4 glasses of milk or water. DO NOT INDUCE VOMITING. Obtain medical care and hospital treatment immediately. Note to physician: This product is highly injurious to all tissues, similar to that of ammonia or ammonia gas. Chemical pneumonitis, pulmonary edema, laryngeal edema and delayed scarring of the airway or other affected tissues may occur following exposure. There

is no specific treatment. Clinical management is based on supportive treatment, which is similar to that for thermal burns.

## VI. REACTIVITY DATA

STABILITY: \*stable\*

HAZARDOUS POLYMERIZATION: \*will not occur\*

### INCOMPATIBILITY:

Oxidizing agents, cleaning solutions, such as chromerge (sulfonic acid/dichromate) and aqua regia. A reaction accompanied by large heat release occurs when the product is mixed with acids. Heat generated may be sufficient to cause vigorous boiling creating a hazard due to splashing or splattering of hot material. CAUTION! N-Nitrosamines, many of which are known to be potent carcinogens, may be formed when the product comes in contact with nitrous acid, nitrites or atmospheres with high nitrous oxide concentrations.

### HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide, Carbon Dioxide and Nitrogen Oxides in a fire. Nitrogen Oxide can react with water vapors to form corrosive nitric acid (TLV= 2 ppm). Combustion of product under oxygen-starved conditions can be expected to produce numerous toxic products including: nitiles, amides. Irritating and toxic fumes at elevated temperatures.

CONDITIONS TO AVOID: Avoid acid contamination and skin contact. Keep containers tightly closed. No smoking or eating in handling area.

## VII. SPILL OR LEAK PROCEDURES

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition (flames, hot surfaces and electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. Use non-sparking tools. Remove with inert absorbant.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

## VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: In confined areas of poor ventilation, use chemical cartridge respirator or self-contained breathing apparatus.

VENTILATION: Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV and LEL of most hazardous ingredient in Section II, below acceptable limit.

### PROTECTIVE GLOVES:

Wear suitable gloves (S37). Nitrile rubber gloves. In

emergency situations, wear impermeable gloves with cuffs to prevent spread of material to area above the wrists.

**EYE PROTECTION:**

Splash proof eye goggles. In emergency situations, use eye goggles with a full face shield.

**OTHER PROTECTIVE EQUIPMENT:**

Wear suitable clothing. Long sleeved clothing.

**HYGIENIC PRACTICES:** See Section V

### IX. SPECIAL PRECAUTIONS

**PRECAUTIONS TO BE TAKEN DURING HANDLING AND STORING:** Do not store near heat, sparks, flame, strong oxidizing agents or strong acids. This material may cause sensitization. Do not get in eyes, on skin or clothing. Do not allow contaminated clothing to contact skin. Avoid contact with vapors or fumes.

**OTHER PRECAUTIONS:** Eye wash station and safety shower should be available

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

Ingredient	CAS #	Wt% of HAPS in product	Pounds HAPS/ Gal product
-----	-----	-----	-----
Xylene	1330-20-7	49.6 %	3.8
Ethyl Benzene	100-41-4	7.7 %	0.6

---