

FastTurn INTERIOR LATEX



Formulated for use as a finish coat on residential or commercial interior surfaces constructed of plaster, wallboard, or wood.



Produces an Appealing, Economical Finish

FastTurn Interior Latex Flat is designed for new construction and multi-family repaints where an economical finish system is required. With its absolute flat appearance, FastTurn minimizes drywall imperfections and produces an appealing, even surface. It makes for an outstanding base coat for subsequent finishes. FastTurn's terrific touch-up qualities reduce labor costs and frustrations on the job site, allowing you to cover your surfaces quickly, and make them look great.



PHYSICAL PROPERTIES	FLAT
Finish	0-5 @ 85°
Resin Type	Vinyl Acrylic
Dry Time to Touch	1 to 2 hours at 70°F and 50% Relative Humidity
Dry Time to Recoat	4 hours at 70°F and 50% Relative Humidity
Recommended Dry Film Thickness per Coat	3.0 to 4.0 mils
Practical Coverage at Recommended DFT	157 to 209 ft²/gallon
Solids by Volume	39%
VOCs	See Technical Data Sheet



OUR FAMILY'S COMMITMENT TO YOU

Andrew Vogel, our founder, decided that the paint he perfected himself was the only paint good enough for houses and barns in the harsh and varied Midwest climate. In 1926, a paint company was born from a modest workshop laboratory. Four generations and millions of gallons of paint later, we still carry on the legacy of our founder. Through our manufacturing facilities, stores, and dealers, we continue to provide the outstanding value and service that our company was built on. From perfecting our own formulas to producing and distributing our own products, our commitment and passion continues to be worthy of Andrew's name.

21758-DV (65833) 01/23



1110 Albany Place SE • Orange City, IA 51041 (712) 737-8880 • architectural@diamondvogel.com/diamondvogel.com/architectural