



Formulated for use on residential or commercial exteriors on new and previously painted wood, hardboard, vinyl siding, cement board, aluminum, galvanized metal, and masonry surfaces down to 35°F. Ideal for use on siding, gutters, soffits, and foundations.



## The Ultimate in Protection and Appearance

Permacryl Exterior Acrylic Latex delivers exceptional quality and value. Its formulated for superior performance while offering extraordinary fade resistance and durability, and provides years of hassle-free living. It offers extremely forgiving application by brush, roller, and spray. Permacryl Exterior allows for application in temperatures as low as 35°F, maximizing application flexibility and extending the painting season. It is perfect for both residential and commercial projects.



| PHYSICAL PROPERTIES                     | FLAT   | SATIN                 | SEMI-GLOSS            |
|---|--|-----------------------|-----------------------|
| Finish                                  | 5-10 @ 85°   | 15-20 @ 60°           | 30-40 @ 60°           |
| Resin Type                              | Acrylic Latex  |                       |                       |
| Dry Time to Touch                       | 30 minutes to 2 hours at > 50°F and 50% Relative Humidity 2 to 4 hours at 35°F to 49°F and 50% Relative Humidity |                       |                       |
| Dry Time to Recoat                      | 2 to 4 hours at > 50°F and 50% Relative Humidity<br>24 hours at 35°F to 49°F and 50% Relative Humidity           |                       |                       |
| Recommended Dry Film Thickness per Coat | 1.5 to 2.0 mils  |                       |                       |
| Practical Coverage at Recommended DFT   | 320 to 427 ft²/gallon  | 305 to 407 ft²/gallon | 289 to 385 ft²/gallon |
| Solids by Volume                        | 40%  | 38%                   | 36%                   |
| VOCs                                    | See Technical Data Sheet   |                       |                       |



## **OUR FAMILY'S COMMITMENT TO YOU**

Our founder, Andrew Vogel, decided that the only paint good enough for the barns and homes in the varied and often harsh Midwest climate was paint he perfected himself. So in 1926, from a modest "workshop laboratory," a paint company was born. Four generations, seven manufacturing

facilities, 64 paint stores, and millions of gallons of paint later, we are still as stubborn. We still insist on perfecting our own formulas, producing and distributing our own products, and servicing our customers with the kind of passion and commitment worthy of Andrew's name.

22311-DV (44695) 01/20



1110 Albany Place SE • Orange City, IA 51041 (712) 737-8880 diamondvogel.com/architectural