

Diamond Vogel®

Eas-E-Poxy

PRE-CATALYZED WATERBORNE EPOXY



Eas-E-Poxy combines ease of use with a tough, long-lasting finish perfect for areas subject to a lot of traffic and abuse.

For use on interior surfaces, masonry surfaces, composites, ferrous metal, and galvanized products.

Eas-E-Poxy

A highly adaptable, single-pack, pre-catalyzed waterborne acrylic epoxy coating. It provides outstanding durability and flexibility. It is non-yellowing, even in industrial environments covering a vast range of potential applications. Eas-E-Poxy is available in a broad spectrum of colors and provides dazzling color retention— making your project look great for years.

FEATURES

- Enhanced abrasion and chemical resistance compared to ordinary latex finishes, offering extra protection
- Applies great by brush, roller, or spray
- Just open and apply, no mixing necessary
- Store it and use it later, making touch-ups easy

FIELD OF APPLICATION

Interior surfaces of health care facilities, equipment, locker rooms, structural or support steel, schools, processing plants, and institutions



PHYSICAL PROPERTIES	EGGSHELL	SEMI-GLOSS
Finish	25–35 @ 85°	35–40 @ 60°
Resin Type	Acrylic Epoxy	
Dry Time to Touch	30 minutes to 2 hours at 70°F and 50% Relative Humidity	
Dry Time to Recoat	2 to 4 hours at 70°F and 50% Relative Humidity	
Recommended Dry Film Thickness per Coat	2.0 to 3.0 mils	
Practical Coverage at Recommended DFT	197 to 297 ft ² /gallon	192 to 289 ft ² /gallon
Solids by Volume	37%	36%
VOCs	See Technical Data Sheet	

33692-DV (65219) 12/22