

Diamond  Vogel®

Hyperprime®

2K ULTRA EPOXY PRIMER SYSTEM



The **Hyperprime** 2K Ultra Epoxy Primer system is a fast-drying, high-performance, high-solids primer.

For original equipment manufacturers that require excellent gloss holdout, adhesion, chip resistance, and corrosion resistance.



Hyperprime 2K Ultra Epoxy Primer System

The Hyperprime 2K Epoxy Primer system is a fast-drying, high-performance, high-solids primer for original equipment manufacturers that require excellent gloss holdout, adhesion, chip resistance, and corrosion resistance. Hyperprime is also available in a Zinc Rich package that features excellent corrosion resistance.

FEATURES

- Excellent gloss holdout
- Chip and corrosion resistance
- Available in multiple packages

FIELD OF APPLICATION

Hyperprime 2K Ultra Epoxy Primer can be sprayed with all types of application equipment. For airless application, no reduction is necessary. For conventional air spray, some reduction may be necessary. For best results, dry film thickness should be 1.0 to 2.0 mils above surface profile. This requires wet film thickness of about 3.0 to 4.0 mils. Apply in one wet coat.

PHYSICAL PROPERTIES

Weight Solids:	60%
Volume Solids:	41%
Resin Type:	Epoxy
Gloss:	Semi-Gloss
Theoretical Coverage:	642 sq. ft./gallon at 1.0 mil
Weight Per Gallon:	10.8 lbs.
Viscosity at 77°F:	30 to 38 seconds #2 Zahn

* For VOC information, see Technical Data Sheet



1020 Albany Place SE • Orange City, IA 51041
(712) 737-4993
diamondvogel.com/industrial

34468-DV (44957) 01/20