

Diamond  Vogel®

ElitePUR

TWO-COMPONENT ACRYLIC POLYURETHANE



ElitePUR is a two-component acrylic polyurethane developed from advanced European technology.

For use on wood surfaces in restaurants, kitchens, and bathroom areas. For surfaces that need the highest resistance to chemicals and abrasion.

ElitePUR Two-Component Acrylic Polyurethane

ElitePUR is a polyurethane of the highest quality with good scratch resistance, smooth tactile surface, and excellent clarity even on darker backgrounds.

FEATURES

- Smooth tactile surface for tabletops
- Excellent clarity even on darker colors
- Superior resistance to abrasion, water, staining, household chemicals, and body oils
- Meets or exceeds AWI & KCMA standards
- Resists the effects of natural light and UV exposure
- Provides superior color and gloss retention

FIELD OF APPLICATION

For surfaces that need the highest resistance to chemicals and abrasion, such as wood surfaces in restaurants, kitchens, and bathroom areas.

PHYSICAL PROPERTIES

Weight:	7.8 to 7.9 lb/gal	
Viscosity at 77°F:	26 to 32 seconds #2 Zahn	
Solids Weight:	28 to 30%	
Solids Volume:	22 to 23%	
Theoretical Coverage:	353 sq. ft./gal after catalyzing	
Flash Point:	41°F	
Gloss at 60°:	Gloss	62 to 70
	Semi-Gloss	50 to 55
	Satin	30 to 40
	Dull Satin	20 to 25
	Flat	3 to 10
Catalyst:	CG-0271 (10:1 Mix Ratio)	

* For VOC information, see Technical Data Sheet



34597-DV (65463) 04/23