

Diamond  Vogel®

EuroCat

PRE-CATALYZED LACQUER



Euro Cat is a single component, high performance pre-catalyzed lacquer for the general wood finishing market.

For use on wood surfaces, kitchen cabinets, restaurant and store fixtures, furniture, and fine architectural woodwork.

EuroCat Pre-Catalyzed Lacquer

EuroCat is a single-component, high-performance pre-catalyzed lacquer for the general wood finishing market. EuroCat contains the qualities of traditional lacquer but provides a harder surface that better resists abrasion. EuroCat is available in a clear or pigmented white finish.

FEATURES

- Superior performance to standard nitrocellulose lacquers without having to add catalyst
- Self-sealing technology
- Fast dry to sand and stack

FIELD OF APPLICATION

- Wood surfaces in kitchens
- Restaurants
- Store fixtures
- Furniture
- Interior wood products



PHYSICAL PROPERTIES	CLEAR FINISH	PIGMENTED FINISH
Weight	7.7 to 7.8 lb/gal	9.0 to 9.4 lb/gal
Viscosity at 77°F	22 to 25 seconds #2 Zahn	24 to 30 seconds #2 Zahn
Solids Weight	27 to 28%	44 to 49%
Solids Volume	19 to 20%	25 to 29%
Theoretical Coverage	320 sq. ft./gal	
Flash Point	41°F	48°F
Gloss at 60°	Gloss = 90+ Semi-Gloss = 55 to 60 Satin = 30 to 35 Dull Satin = 20 to 25 Flat = 10	Gloss = 70+ Semi-Gloss = 55 to 60 Satin = 38 to 42 Dull Satin = 20 to 25

* For VOC information, see Technical Data Sheet