



# Workhorse Primer

UNIVERSAL PRIMER SYSTEM



**Workhorse Universal Primer** is a versatile primer that can be used in conjunction with a variety of topcoats and is ideal for structural and industrial uses.

Exhibits fast dry times, good gloss holdout, corrosion resistance, and lift-resistant properties.



## Workhorse Universal Primer System

The Workhorse Universal Primer System exhibits fast dry times, good gloss holdout, corrosion resistance, and lift-resistant properties. This system is ideal for structural shop and industrial uses. Workhorse Universal Primer can be top coated with epoxy, vinyl, chlorinated rubber, alkyd, acrylic, and urethane coatings as well as conventional oil and oleoresinous topcoats.

### FEATURES

- Exhibits fast dry times and good gloss holdout
- Versatile with a variety of topcoat technologies
- Corrosion-resistant and lift-resistant properties

### FIELD OF APPLICATION

The Workhorse Universal Primer System can be sprayed with all types of application equipment. For best results, dry film thicknesses should be about 1.0 to 2.0 mils above the surface profile. This will require a wet film thickness of around 2.0 to 4.0 mils.

### PHYSICAL PROPERTIES

Weight Solids:	72% to 75%
Volume Solids:	50% to 54%
Resin Type:	Modified Alkyd
Gloss:	Flat
Theoretical Coverage:	800 to 870 sq. ft. at 1.0 mil
Weight Per Gallon:	12.7 to 13.1 lbs
Viscosity at 77° F:	16 to 18 seconds #3 Zahn
VOCs:	2.8 lbs. per gallon



1020 Albany Place SE • Orange City, IA 51041  
(712) 737-4993  
[diamondvogel.com/industrial](http://diamondvogel.com/industrial)

40657-DV (44956) 01/20

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Diamond Vogel does not control the application of its products or the condition of the surfaces to which they are applied, Diamond Vogel's liability will under no circumstances exceed replacement of the product. All technical information is subject to change without notice.