

Diamond Vogel®

Durango™

ACRYLIC LATEX EXTERIOR FINISH



Durango Acrylic Latex Exterior Finish
offers outstanding application and durability
while delivering long-lasting value.

Formulated for use on new or previously painted wood, hardboard, vinyl siding, cement board, aluminum, galvanized metal, and masonry surfaces. Ideal for use on siding, gutters, soffits, and foundations.



Outstanding Durability, Exceptional Value

Durango Acrylic Latex Exterior Finish offers outstanding durability and value for new construction and repaints on residential and commercial projects. Its enhanced flexibility guards against cracking and peeling, and acrylic technology provides superior fade resistance to deliver a long-lasting finish.

15-Year Limited Warranty

We want you to be completely satisfied with Durango and how it performs on your home.

We know you will be, and we guarantee it.

Diamond Vogel provides a 15-year limited warranty for this product when used according to label instructions, that the product will not blister or peel from a properly prepared and primed surface. If the product peels or blisters within 15- years of the date of purchase, Diamond Vogel will, upon proof of purchase, provide replacement coatings at no charge to repair the affected area. This limited warranty is non-transferrable. Since we have no control over surface preparation or application, this limited warranty does not include the labor costs for the application or removal of paint. Diamond Vogel shall not be liable for any indirect, special, incidental, or consequential damages. Some states do not allow the exclusion of limitation or consequential damages, so the limitations and exclusions may not apply to you. This warranty gives you specific legal rights, and you may have other rights which vary from state to state.



PHYSICAL PROPERTIES	FLAT	SATIN
Finish	0-5 @ 85°	25-30 @ 85°
Resin Type	Acrylic	
Dry Time to Touch	30 minutes to 2 hours at >50°F and 50% Relative Humidity 2 to 4 hours at 35°F to 49°F and 50% Relative Humidity	
Dry Time to Recoat	2 to 4 hours at >50°F and 50% Relative Humidity 24 hours at 35°F to 49°F and 50% Relative Humidity	
Recommended Dry Film Thickness per Coat	1.5 to 2.0 mils	
Practical Coverage at Recommended DFT	276 to 363 ft ² /gallon	
Solids by Volume	34%	
VOCs	See Technical Data Sheet	



OUR FAMILY'S COMMITMENT TO YOU

Andrew Vogel, our founder, decided that the paint he perfected himself was the only paint good enough for houses and barns in the harsh and varied Midwest climate. In 1926, a paint company was born from a modest workshop laboratory. Four generations and millions of gallons of paint later, we still carry on the legacy of our

founder. Through our manufacturing facilities, stores, and dealers, we continue to provide the outstanding value and service that our company was built on. From perfecting our own formulas to producing and distributing our own products, our commitment and passion continues to be worthy of Andrew's name.

46935-DV (64915) 12/22



ARCHITECTURAL
COATINGS

1110 Albany Place SE • Orange City, IA 51041
(712) 737-8880 • architectural@diamondvogel.com
diamondvogel.com/architectural