

## TECHNICAL BULLETIN Finishing Exterior Plywood

The challenge of finishing plywood is to overcome the tendency toward face-checking and coating failure as a result of the stresses induced by dimensional changes during wet-dry moisture cycling. There are basically three options:

## **Option 1**

Use a penetrating finish that does not form a surface film and therefore cannot fail by checking and flaking. High quality semitransparent stains highlight the architectural intent of textured plywood siding. They add color and beauty to the plywood siding, showing off its rustic, rough texture. The wood grain and other natural characteristics, such as color differences in the wood, show through the finish. However, be aware that repairs which have been made on the veneer face of the plywood will also show.

We recommend two coats of Diamond Vogel's **Grain Stain Semi-Transparent Stain** or **Grain Stain Semi-Solid Stain** be applied to rough texture plywood. Note, you need to allow time for the first coat to soak into the wood, but the second coat has to be applied before the first coat dries. Any excess after the application of the second coat should be removed with a dry brush or a sponge to make sure the application is even with no lap marks. A full panel should be done at one time to keep down the possibility of lap marks.

## **Option 2**

Use solid color stains for a flexible coating when you want to cover the grain and color of the wood, as well as surface repairs, but your desire is for the texture of the wood to show through. Two coats of **Grain Stain Solid Latex Stain** are recommended for use on plywood. The plywood should be primed with Diamond Vogel's **Sure Grip Exterior Acrylic Latex Primer** tinted and top coated with one or two coats of **Grain Stain Solid Latex Stain**.

## **Option 3**

Use a high quality acrylic latex paint that is sufficiently flexible to withstand dimensional changes in the wood and helps to protect against the checking and cracking that occurs in the face veneer. Acrylic latex paints offer the best protection and the greatest durability for plywood Diamond Vogel's **Palisade Ultra Premium Exterior Acrylic Latex, Durango Acrylic Latex Exterior Finish,** or **EverCryl Exterior Acrylic Latex Finish** are recommended if you want to paint the plywood. Again, we recommend that it be primed with a coat of **Sure Grip Exterior Acrylic Latex Prime**r tinted to the color of the finish coat, followed by two coats of **Palisade Ultra Premium Exterior Acrylic Latex, Durango Acrylic Latex Exterior Finish,** or **EverCryl Exterior Acrylic Latex Finish**.

47108-DV (54853) 07/21

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of the surfaces to which they are applied, Diamond Vogel's liability will under no circumstances exceed replacement of the product.