

TECHNICAL BULLETIN Painting Cement Siding

Cement siding (a popular brand name is Hardie Board) is exactly as it sounds. It has the appearance of wood or hardboard siding with the benefits of cement. Cement siding gives you the warmth of wood and the durability of fiber cement. It resists moisture damage, is low maintenance, won't rot or delaminate like wood or hardboard, and withstands termite attack. Cement siding is a durable attractive alternative to wood, composite, cedar, vinyl, brick, or stucco siding. Cement siding will give you years of low maintenance when painted with a quality paint system.

Preparation

Patch all dents, chips and cracks with a patching material such as Durham's Rock Hard Putty. Prior to painting, clean cement siding with a low-pressure water spray or a medium bristle (nonmetal) brush. Let the surface dry for 2-4 days after washing. If you are re-painting cement board siding, be sure to remove all contaminants such as dirt, grime and chalk prior to painting.

Painting Options

Repaint: On a repaint job, spot prime any bare areas with an acrylic primer such as Diamond Vogel **Sure Grip Interior**/ **Exterior Acrylic Latex Primer** followed by one or two coats of acrylic latex paint such as Diamond Vogel **Palisade Ultra Premium Exterior Acrylic Latex, Durango Acrylic Latex Exterior Finish,** or **EverCryl Exterior Acrylic Latex Finish.**

Pre-primed: Some cement siding companies offer their siding with a pre-primed option. In this case, be sure the surface is clean and free of all contaminants and finish with one or two coats of acrylic latex paint such as Diamond Vogel **Palisade Ultra Premium Exterior Acrylic Latex, Durango Acrylic Latex Exterior Finish,** or **EverCryl Exterior Acrylic Latex Finish.** Apply two coats for increased durability.

Unprimed: When painting unprimed cement siding, follow the preparation instructions above prior to painting. Use an acrylic primer such as Diamond Vogel's **Sure Grip Interior/Exterior Acrylic Latex Primer** and then finish with acrylic latex paint such as Diamond Vogel's **Palisade Ultra Premium Exterior Acrylic Latex, Durango Acrylic Latex Exterior Finish,** or **EverCryl Exterior Acrylic Latex Finish.** For increased durability, two coats of finish are recommended.

For further information on painting cement siding, contact your Diamond Vogel representative.

47109-DV 01/23

Diamond Vogel | Architectural Coatings 1110 Albany Place SE • Orange City, IA 51041 (712) 737-8880 • architectural@diamondvogel.com

diamondvogel.com/architectural

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Diamond Vogel does not control the application of its products or the condition of the surfaces to which they are applied, Diamond Vogel's liability will under no circumstances exceed replacement of the product. All technical information is subject to change without notice.