

Aisle Ease LATEX SAFETY MARKING



HIGH PERFORMANCE

Aisle Ease Gloss Latex Safety Marking

> MC-3609 Yellow

WARNING! VAPOR HARMFUL. CAUSES EYE AND SKIN IRRITATION. MAY BE HARMFU IF ABSORBED THROUGH SKIN. HARMFUL IF SWALLOW See other cautions on back panel. **Aisle Ease** is a fast drying, long lasting, cost-effective solution for floor safety markings.

Apply to interior or exterior surfaces such as traffic aisles, staging areas, masonry surfaces, safety zones, or walkways.

Aisle Ease

Aisle Ease provides a highly cost-effective solution for floor safety markings in factories and warehouses. It is carefully formulated to eliminate downtime, allowing foot traffic in as quickly as 90 minutes. By taking advantage of a latex formulation, Aisle Ease is very low odor, allowing for work to continue nearby while painting is underway. The gloss sheen enhances the appearance of the marking and provides a cleanable surface, reducing the need for recoating.

FEATURES

- Bright visible lines
- Resistance to dirt pick up
- Easy cleaning
- Increased safety and awareness
- Available in white and yellow

FIELD OF APPLICATION

Apply to interior or exterior surfaces such as traffic aisles, staging areas, masonry surfaces, safety zones, or walkways.



PHYSICAL PROPERTIES	White	Yellow
Finish	Gloss, 60+ @ 60°	
Resin Type	Acrylic Latex	
Dry Time to Touch	30 minutes at 70°F and 50% Relative Humidity	
Dry Time to Recoat	30 minutes at 70°F and 50% Relative Humidity	
Dry Time for Foot Traffic	1.5 hours at 70°F and 50% Relative Humidity	
Dry Time for Full Traffic	12 hours at 70°F and 50% Relative Humidity	
Recommended Dry Film Thickness per Coat	3.0 to 4.0 mils	
Practical Coverage at Recommended DFT	94 to 123 ft ² /gallon, 4" wide line 457 to 609 lineal feet per gallon	
Solids by Volume	38%	
VOCs	See Technical Data Sheet	

50259-DV (65828) 01/23

