

Diamond  Vogel®

# Vers-E-Poxy 131

WATERBORNE ACRYLIC EPOXY



**Vers-E-Poxy 131** makes it easy to provide additional protection in tough environments.

Offers protection in shower/locker rooms, operating rooms, laboratories, processing plants, schools, institutions, and material handling facilities.

## Vers-E-Poxy 131

**Vers-E-Poxy 131** is a two-component, water-based, catalyzed, acrylic epoxy coating formulated to provide high-performance protection in industrial and commercial environments. It provides impact, abrasion, and chemical resistance and can be used on both interior and exterior substrates. Vers-E-Poxy 131 has outstanding application properties and is an excellent choice for upgrading conventional coatings to a high-performance protection system when required.

### FEATURES

- Impact resistant
- Abrasion resistant
- Chemical resistant
- Outstanding application properties
- Interior and exterior substrates
- Available in semi-gloss and gloss

### FIELD OF APPLICATION

Can offer protection in environments such as shower/locker rooms, operating rooms, laboratories, processing plants, schools, institutions, and material handling facilities.



PHYSICAL PROPERTIES	SEMI-GLOSS	GLOSS
Finish	25–30 @ 60°	Gloss 70+ @ 60°
Resin Type	Two-Component Acrylic Latex Epoxy	
Dry Time to Touch	30 minutes at 70°F and 50% Relative Humidity	
Dry Time to Recoat	Minimum 4 hours at 70°F and 50% Relative Humidity	
Recommended Dry Film Thickness per Coat	5.5 to 6.5 mils	6.0 to 7.0 mils
Practical Coverage at Recommended DFT	243–304 ft <sup>2</sup> /gallons	224–280 ft <sup>2</sup> /gallons
Solids by Volume	38%	35%
VOCs	See Technical Data Sheet	

50406-DV (67221) 04/23