



# PUR Coatings

TWO-COMPONENT ACRYLIC POLYURETHANE



**The PUR line of coatings** are two-component polyurethane acrylics that provide a range of finishing options that are tough, durable, and beautiful.

For use on furniture, fine architectural woodwork, and wood surfaces in restaurants, kitchens, and bathrooms. Use on surfaces that need the highest resistance to chemicals and abrasion.

# PUR Coatings

## A full line of solutions

The PUR product line offers a variety of options, all featuring the strength, durability, and beauty that come with using a full family of two-component polyurethane coatings. The product line offers a range of appearances and physical properties to fit a wide variety of applications, from wood surfaces in restaurants to use in kitchens and bathrooms. Preparation and protection go even further with multiple priming and sealing options.



ElitePUR	MultiPUR Clear	MultiPUR Pigmented	NaturalPUR
Clear	Clear	Opaque	Clear
The best performance in the PUR line; water-white with superior resistance to abrasion, impact, and chemicals.	The most versatile application options, while still providing a high performing clear finish.	The flexible choice for a pigmented finish, providing unmatched color development when paired with a primer.	The performance of the PUR line with an almost invisible appearance, for the natural European oil rubbed look.
<b>Gloss at 60°:</b> Gloss 62 to 70 Semi-Gloss 50 to 55 Satin 30 to 40 Dull Satin 20 to 25 Flat 3 to 10	<b>Gloss at 60°:</b> Gloss 80+ Semi-Gloss 55 to 60 Satin 38 to 42 Dull Satin 20 to 25 Flat 3 to 7	<b>Gloss at 60°:</b> Gloss 75+ Satin 35 to 40 Dull Satin 20 to 25 Flat 10 to 15	<b>Gloss at 60°:</b> Dull Matte 0 to 4

Catalyst (Mix Ratio)	CG-0271 (10:1)	CG-0270 (10:1 or 5:1)	CG-0270 (10:1)	CG-0270 (10:1)
Weight	7.8 to 7.9 lb/gal	7.7 to 7.8 lb/gal	9.16 lb/gal	7.8 lb/gal
Viscosity at 77°F (#2 Zahn)	26 to 32 seconds	20 to 39 seconds	25 to 35 seconds	27 to 33 seconds
Solids Weight	28 to 30%	25 to 28%	41%	20%
Solids Volume	22 to 23%	20 to 22%	27%	15%
Theoretical Coverage after catalyzing	353 sq. ft./gal	320 sq. ft./gal	320 sq. ft./gal	353 sq. ft./gal
Flash Point	41°F	41°F	41°F	41°F

\*For VOC information, see Technical Data Sheet





PUR Neutral Primer		PUR White Primer		Isolation 680		PUR Sealer	
Primer		Primer		Sealer		Sealer	
The best option in tinting medium to dark colors to look their best under the chosen topcoat.		The best option in preparing light colors; tintable to match the desired topcoat.		The best adhesion a sealer can offer, especially with naturally oily woods like teak or rosewood.		The standard sealer in the PUR line of coatings.	
<b>Gloss at 60°:</b> Primer 0 to 5		<b>Gloss at 60°:</b> Primer 0 to 5		<b>Gloss at 60°:</b> Gloss 90+		<b>Gloss at 60°:</b> Dull Satin 28 to 32	
CG-0270 (10:1)		CG-0270 (10:1)		CG-0275 (2:1)		CG-0271 (10:1)	
8.3 lb/gal		9.4 lb/gal		8.13 lb/gal		8.0 lb/gal	
40 to 50 seconds		40 to 45 seconds		12 to 15 seconds		30 to 35 seconds	
34%		46%		32%		33%	
26%		30%		24%		27%	
320 sq. ft./gal		320 sq. ft./gal		392 sq. ft./gal		433 sq. ft./gal	
41°F		41°F		70°F		81°F	



## PUR Coatings

### FEATURES

- Excellent clarity on a wide variety of background colors
- Superior resistance to abrasion, water, staining, household chemicals, and body oils
- Resists natural light and UV exposure, providing superior color and gloss retention
- Smooth tactile surface\*
- Fast drying
- Provides exceptional adhesion and sandability
- Meets or exceeds AWI and KCMA standards

### FIELD OF APPLICATION

Wood surfaces in restaurants, kitchens, and bathroom areas. Suitable for store fixtures, furniture, and fine architectural woodwork. For surfaces that need the highest resistance to chemicals and abrasion.



\*Contact a Diamond Vogel representative to discuss the best methods to achieve desired results.



### OUR FAMILY'S COMMITMENT TO YOU

Andrew Vogel, our founder, decided that the paint he perfected himself was the only paint good enough for houses and barns in the harsh and varied Midwest climate. In 1926, a paint company was born from a modest workshop laboratory. Four generations and millions of gallons of paint later, we still carry on the legacy of our

founder. Through our manufacturing facilities, stores, and dealers, we continue to provide the outstanding value and service that our company was built on. From perfecting our own formulas to producing and distributing our own products, our commitment and passion continues to be worthy of Andrew's name.

65500-DV (71062) 04/24



INDUSTRIAL  
WOOD COATINGS

710 Forest Avenue • Sheboygan Falls, WI 53085  
(920) 467-7850 • [industrialwood@diamondvogel.com](mailto:industrialwood@diamondvogel.com)  
[diamondvogel.com/industrialwood](http://diamondvogel.com/industrialwood)

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Diamond Vogel does not control the application of its products or the condition of the surfaces to which they are applied, Diamond Vogel's liability will under no circumstances exceed replacement of the product. All technical information is subject to change without notice.