

Diamond  Vogel®

# UniFill Pro

INTERIOR / EXTERIOR ACRYLIC BLOCK FILLER



**UniFill Pro** is designed to prime and fill interior and exterior porous concrete block and cinder block, providing a smooth, consistent finish for the final coat.

Formulated as a prime coat for all types of porous concrete and cinder block.



# Optimized for a Smooth, Uniform Finish

**UniFill Pro Interior/Exterior Acrylic Block Filler** primes and fills interior and exterior porous concrete block and cinder block. It creates a smooth, uniform finish that aids in sheen consistency and enhances the finish coat. UniFill Pro fills pinholes and seals voids in concrete, resulting in improved coating performance. It is optimized to make filling in the block's pores easier when backrolling. UniFill Pro is compatible with both water-based and solvent-based finishes.

Performance criteria meet or exceed Master Painters Institute (MPI) #4 approval standards.



PHYSICAL PROPERTIES	FLAT
Finish	<5 @ 85°
Resin Type	Acrylic Latex
Dry Time to Touch	2 hours at 70°F and 50% Relative Humidity
Dry Time to Recoat	4 hours at 70°F and 50% Relative Humidity
Recommended Dry Film Thickness per Coat	5.0 to 15.0 mils
Practical Coverage at Recommended DFT	53 to 160 ft <sup>2</sup> /gallon
Solids by Volume	50%
VOCs	See Technical Data Sheet



## OUR FAMILY'S COMMITMENT TO YOU

Andrew Vogel, our founder, decided that the paint he perfected himself was the only paint good enough for houses and barns in the harsh and varied Midwest climate. In 1926, a paint company was born from a modest workshop laboratory. Four generations and millions of gallons of paint later, we still carry on the legacy of our

founder. Through our manufacturing facilities, stores, and dealers, we continue to provide the outstanding value and service that our company was built on. From perfecting our own formulas to producing and distributing our own products, our commitment and passion continues to be worthy of Andrew's name.

69493-DV (69493) 03/24



ARCHITECTURAL COATINGS

1110 Albany Place SE • Orange City, IA 51041  
(712) 737-8880 • architectural@diamondvogel.com  
diamondvogel.com/architectural

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Diamond Vogel does not control the application of its products or the condition of the surfaces to which they are applied, Diamond Vogel's liability will under no circumstances exceed replacement of the product. All technical information is subject to change without notice.