# SAFETY DATA SHEET

Revision Date 25-Oct-2022

Diamond

Version 5

# **1. IDENTIFICATION**

Product identifier Product Name

Grain Stain Semi-Transparent French White Oil Stain

Other means of identification Product Code SKU(s)

AG-1319 None

Recommended use of the chemical and restrictions on useRecommended UseNo information available.Uses advised againstNo information available

Details of the supplier of the safety data sheet Manufacturer Address Diamond Vogel 1020 Albany Place SE Orange City, IA 51041 Phone: (712) 737-4993 Fax: (712) 737-4997

Emergency telephone number Emergency Telephone

Chemtrec 1-800-424-9300

# 2. HAZARDS IDENTIFICATION

# **Classification**

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Aspiration toxicity	Category 1
Flammable liquids	Category 3

**Emergency Overview** 

# Danger

# Hazard statements

May cause an allergic skin reaction May cause genetic defects May cause cancer May be fatal if swallowed and enters airways Flammable liquid and vapor



# **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed Ground/bond container and receiving equipment Use only non-sparking tools Take precautionary measures against static discharge Use explosion-proof electrical/ ventilating/ lighting/ equipment

# Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam for extinction

# **Precautionary Statements - Storage**

Store locked up Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

- Other Information
- Causes mild skin irritation
- · Harmful to aquatic life with long lasting effects
- Harmful to aquatic life

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%	Trade Secret
Solvent Naphtha, Medium Aliphatic	64742-88-7	30 - 60	*
Linseed Oil	8001-26-1	10 - 30	*
Titanium dioxide	13463-67-7	5 - 10	*
1,2,4-Trimethylbenzene	95-63-6	1 - 5	*
Xylene	1330-20-7	1 - 5	*
3-iodo-2-propynyl butyl carbamate	55406-53-6	0.1 - 1	*
Ethyl Benzene	100-41-4	0.1 - 1	*

# AG-1319 Grain Stain Semi-Transparent French White Oil Stain

Aromatic	100	64742-95-6	0.1 - 1	*	
Mineral Sp	Spirits 64742-48-9		0.1 - 1	*	
Cobalt 2-ethylh	exanoate	anoate 136-52-7 0.1 - 1 *			
Stoddard So	olvent	8052-41-3	0.1 - 1	*	
*The exa	ct percentage (concent	ration) of composition has I	been withheld as a trade s	secret.	
	4.	FIRST AID MEASURE	ES		
Description of first aid mea	sures				
Eye contact		Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.			
Skin Contact	Call a physici	Call a physician immediately.			
Inhalation		Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.			
Ingestion		Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to ar unconscious person. Get medical attention.			
Most important symptoms a	and effects, both acute	e and delayed			
Symptoms	No informatio	No information available.			
Indication of any immediate	medical attention and	d special treatment neede	ed		

Note to physicians Treat symptomatically.

# **5. FIRE-FIGHTING MEASURES**

# Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

Flammable. WARNING: Spontaneous combustion (fire) may result from materials such as rags, steel wool, paper, clothing, and other waste soaked in linseed oil. Place in a sealed, water filled, metal container to prevent this.

# Explosion data Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

# Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

# Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Use personal protective equipment as required.

Environmental precautions

Environmental precautions

Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

#### Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.		
Methods for cleaning up	Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak u with inert absorbent material.		
	7. HANDLING AND STORAGE		
Precautions for safe handling			
Advice on safe handling	Avoid contact with skin, eyes or clothing.		
Conditions for safe storage, in	cluding any incompatibilities		
Storage Conditions	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).		

Incompatible materials Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Control parameters

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Titanium dioxide	TWA: 0.2 mg/m <sup>3</sup> nanoscale	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7	respirable particulate matter	TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine
	TWA: 2.5 mg/m <sup>3</sup> finescale		TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine
	respirable particulate matter		including engineered nanoscale
1,2,4-Trimethylbenzene	TWA: 10 ppm	-	TWA: 25 ppm
95-63-6			TWA: 125 mg/m <sup>3</sup>
Xylene	TWA: 20 ppm	TWA: 100 ppm	-
1330-20-7		TWA: 435 mg/m <sup>3</sup>	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m <sup>3</sup>	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m <sup>3</sup>	
Ethyl Benzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>
		(vacated) TWA: 435 mg/m <sup>3</sup>	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m <sup>3</sup>
		(vacated) STEL: 545 mg/m <sup>3</sup>	
Stoddard Solvent	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m <sup>3</sup>
8052-41-3		TWA: 2900 mg/m <sup>3</sup>	Ceiling: 1800 mg/m <sup>3</sup> 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m <sup>3</sup>
		(vacated) TWA: 525 mg/m <sup>3</sup>	

NIOSH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

# Appropriate engineering controls

# Engineering Controls Showers Eyewash stations Ventilation systems.

# Individual protection measures, such as personal protective equipment

Eye/face protection	No special technical protective measures are necessary.
Skin and body protection	No special technical protective measures are necessary.

<b>Respiratory protection</b> If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.						
General Hygiene Considerations						
	9. PHYSICAL AND CHEMICAL PROPERTIES					
Information on basic physical an	d chemical properties					
Physical state	Liquid					
Appearance	No information available	Odor	No information available			
Color	No information available	Odor threshold	No information available			
Property_	Values	Remarks • Method				
pH	No information available					
Melting point / freezing point	No information available					
Boiling point / boiling range	>= 80 °C / 176 °F					
Flash point	39 °C / 102 °F					
Evaporation rate	No information available					
Flammability (solid, gas) Flammability Limit in Air	No information available					
Upper flammability limit:	No information available					
Lower flammability limit:	No information available					
Vapor pressure	No information available					
Vapor density	No information available					
Specific Gravity	0.91					
Water solubility	No information available					
Solubility in other solvents	No information available					
Partition coefficient	No information available					
Autoignition temperature	No information available					
Decomposition temperature	No information available					
Kinematic viscosity	No information available					
Dynamic viscosity	No information available No information available					
Explosive properties Oxidizing properties	No information available					
Other Information						
Softening point	No information available					
Molecular weight	No information available					
Liquid Density	7.57 lbs/gal					
Bulk density	No information available					
Percent solids by weight	39.2%					
Percent volatile by weight	60.1%					
Percent solids by volume	29.9%					
Actual VOC (Ibs/gal)	4.5					
Actual VOC (grams/liter)	545.3					
EPA VOC (lbs/gal)	4.6					
EPA VOC (grams/liter)	548					
EPA VOC (lb/gal solids)	15.2					
	10. STABILITY AND	REACTIVITY				

Reactivity No data available

<u>Chemical stability</u> Stable under recommended storage conditions.

# Possibility of hazardous reactions

None under normal processing.

#### Conditions to avoid

Heat, flames and sparks.

# **Incompatible materials**

Chlorinated compounds.

# Hazardous decomposition products

Carbon oxides.

# **11. TOXICOLOGICAL INFORMATION**

# Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin Contact	No data available.
Ingestion	No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 25 mL/kg (Rat)	> 4000 mg/kg (Rabbit)	> 5.28 mg/L (Rat)4 h
Linseed Oil 8001-26-1	> 15,000 mg/kg	-	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat)4 h
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m³ (Rat)4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h
3-iodo-2-propynyl butyl carbamate 55406-53-6	= 1470 mg/kg (Rat)	> 2000 mg/kg (Rat)	= 0.63 mg/L (Rat) 4 h = 0.67 mg/L (Rat) 4 h = 0.99 mg/L (Rat) 4 h
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat)4 h
Aromatic 100 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat)4 h
Mineral Spirits 64742-48-9	> 6000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 8500 mg/m³(Rat)4 h
Cobalt 2-ethylhexanoate 136-52-7	= 1300 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 10 mg/L (Rat)1 h
Stoddard Solvent 8052-41-3	> 5000 mg/kg (Rat)	> 3000 mg/kg (Rabbit)	> 5.5 mg/L (Rat)4 h

# Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicity	No informatic No informatic			
Carcinogenicity	No information	on available.		
Chemical name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	A3	Group 2B	-	Х

Xylene	-	Group 3	-	-		
1330-20-7						
Ethyl Benzene	A3	Group 2B	-	Х		
100-41-4		•				
Cobalt 2-ethylhexanoate	-	Group 2B	Reasonably Anticipated	Х		
136-52-7		·	, , , , , , , , , , , , , , , , , , ,			
A3 - Animal Carcinogen	erence of Governmental Inc	50 ,				
	ency for Research on Cance	r)				
Group 2B - Possibly Care						
	e as a human carcinogen					
NTP (National Toxicolo Known - Known Carcinoc						
	- Reasonably Anticipated to be	a Human Careinagan				
			at of Labor)			
X - Present	OSHA (Occupational Safety and Health Administration of the US Department of Labor)					
Reproductive toxicity No information available.						
	STOT - single exposure No information available.					
STOT - repeated exposure No information available.						
Chronic toxicity	Chronic toxicity Ethylbenzene has been classified by the International Agency for Research on Cancer					
	(IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated					
	overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory					
	system, thyroid, testicles, and pituitary glands. May cause adverse effects on the bone					
	marrow and l	marrow and blood-forming system.				
Target organ effects	blood, Centra	blood, Central nervous system, Eyes, Lungs, Respiratory system, Skin.				
Aspiration hazard	No information	No information available.				

# Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document  $\,$  mg/kg  $\,$  mg/l  $\,$ 

# **12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

Harmful to aquatic life with long lasting effects

# 9.93% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Solvent Naphtha, Medium Aliphatic	450: 96 h Pseudokirchneriella	800: 96 h Pimephales promelas	100: 48 h Daphnia magna mg/L
64742-88-7	subcapitata mg/L EC50	mg/L LC50 static	EC50
1,2,4-Trimethylbenzene	-	7.19 - 8.28: 96 h Pimephales	6.14: 48 h Daphnia magna mg/L
95-63-6		promelas mg/L LC50 flow-through	ÉC50
Xylene	-	13.1 - 16.5: 96 h Lepomis	0.6: 48 h Gammarus lacustris mg/L
1330-20-7		macrochirus mg/L LC50	LC50 3.82: 48 h water flea mg/L
		flow-through 13.5 - 17.3: 96 h	EC50
		Oncorhynchus mykiss mg/L LC50	
		2.661 - 4.093: 96 h Oncorhynchus	
		mykiss mg/L LC50 static 23.53 -	
		29.97: 96 h Pimephales promelas	
		mg/L LC50 static 30.26 - 40.75: 96	
		h Poecilia reticulata mg/L LC50	
		static 7.711 - 9.591: 96 h Lepomis	
		macrochirus mg/L LC50 static 13.4:	
		96 h Pimephales promelas mg/L	
		LC50 flow-through 19: 96 h Lepomis	
		macrochirus mg/L LC50 780: 96 h	
		Cyprinus carpio mg/L LC50	
		semi-static 780: 96 h Cyprinus	
		carpio mg/L LC50	
3-iodo-2-propynyl butyl carbamate	-	0.049 - 0.079: 96 h Oncorhynchus	-
55406-53-6		mykiss mg/L LC50 flow-through	
		0.05 - 0.089: 96 h Oncorhynchus	
		mykiss mg/L LC50 0.14 - 0.32: 96 h	
		Lepomis macrochirus mg/L LC50	

		flow-through 0.18 - 0.23: 96 h	
		Pimephales promelas mg/L LC50	
		flow-through	
Ethyl Benzene	1.7 - 7.6: 96 h Pseudokirchneriella	11.0 - 18.0: 96 h Oncorhynchus	1.8 - 2.4: 48 h Daphnia magna mg/L
100-41-4	subcapitata mg/L EC50 static 2.6 -	mykiss mg/L LC50 static 7.55 - 11:	EC50
	11.3: 72 h Pseudokirchneriella	96 h Pimephales promelas mg/L	
	subcapitata mg/L EC50 static 4.6:	LC50 flow-through 9.1 - 15.6: 96 h	
	72 h Pseudokirchneriella	Pimephales promelas mg/L LC50	
	subcapitata mg/L EC50 438: 96 h	static 32: 96 h Lepomis macrochirus	
	Pseudokirchneriella subcapitata	mg/L LC50 static 4.2: 96 h	
	mg/L EC50	Oncorhynchus mykiss mg/L LC50	
		semi-static 9.6: 96 h Poecilia	
		reticulata mg/L LC50 static	
Aromatic 100	-	9.22: 96 h Oncorhynchus mykiss	6.14: 48 h Daphnia magna mg/L
64742-95-6		mg/L LC50	EC50
Mineral Spirits	-	2200: 96 h Pimephales promelas	-
64742-48-9		mg/L LC50	

# Persistence and degradability No information available.

# **Bioaccumulation**

No information available.

Chemical name	Partition coefficient
1,2,4-Trimethylbenzene 95-63-6	3.63
Xylene 1330-20-7	2.77 - 3.15
3-iodo-2-propynyl butyl carbamate 55406-53-6	2.88
Ethyl Benzene 100-41-4	3.6
Stoddard Solvent 8052-41-3	6.4

Other adverse effects

No information available

# **13. DISPOSAL CONSIDERATIONS**

Waste treatment methods	
Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
	14. TRANSPORT INFORMATION

DOT

Not regulated

# **15. REGULATORY INFORMATION**

International Inventories		
TSCA	Complies	

# DSL/NDSL

Complies \*

\* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

# Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

# US Federal Regulations

## <u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
1,2,4-Trimethylbenzene - 95-63-6	1.0
Xylene - 1330-20-7	1.0
Ethyl Benzene - 100-41-4	0.1
Cobalt 2-ethylhexanoate - 136-52-7	0.1

## SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

# CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	Х
Ethyl Benzene 100-41-4	1000 lb	X	X	Х

# **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethyl Benzene	1000 lb	-	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

# US State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethyl Benzene - 100-41-4	Carcinogen
Silica, Amorphous fumed - 7631-86-9	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen
Cumene - 98-82-8	Carcinogen
Naphthalene - 91-20-3	Carcinogen
Toluene - 108-88-3	Developmental
Propylene oxide - 75-56-9	Carcinogen
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen
	Developmental
	Male Reproductive

# U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Titanium dioxide 13463-67-7	Х	Х
1,2,4-Trimethylbenzene 95-63-6	Х	Х
Xylene 1330-20-7	Х	Х
Ethyl Benzene 100-41-4	Х	Х
Dimethyl Sulfoxide 67-68-5	Х	-
Cobalt 2-ethylhexanoate 136-52-7	Х	-

Chemical name	Pennsylvania
Linseed Oil	Х
8001-26-1	
Titanium dioxide 13463-67-7	X
1,2,4-Trimethylbenzene 95-63-6	X
Xylene 1330-20-7	X

### U.S. EPA Label Information

# EPA Pesticide Registration Number Not applicable

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present individually at 1% by weight, or greater):

Chemical name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Xylene	1.38%	0.10
1330-20-7		

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 2	Flammability 2	Instability 0	Physical and chemical properties -
HMIS	Health hazards 2 *	Flammability 2	Physical hazards 0	Personal protection X
Chronic Hazard Star Le	egend * = Chroni	c Health Hazard		

Revision Date

25-Oct-2022

**Revision Note** No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

# End of Safety Data Sheet