SAFETY DATA SHEET

Revision Date 15-Jun-2020

Diamond

oqe

Version 3

1. IDENTIFICATION

Product identifier Product Name

PermAcryl Exterior Acrylic Latex Semi-Gloss Deep Base

Other means of identification Product Code SKU(s)

BN-1533 None

Recommended use of the chemical and restrictions on useRecommended UseNo information available.Uses advised againstNo information available

Details of the supplier of the safety data sheetManufacturer AddressDiamond Vogel1020 Albany Place SEOrange City, IA 51041Phone: (712) 737-4993Fax: (712) 737-4997Emergency telephone numberEmergency TelephoneChemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Carcinogenicity	Category 1A

Emergency Overview

Danger		
Hazard statements May cause an allergic skin reaction May cause cancer		
Appearance No information available	Physical state Liquid	Odor No information available

Precautionary Statements - Prevention Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

· Harmful to aquatic life with long lasting effects

Harmful to aquatic life

Unknown acute toxicity

3.04% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Titanium dioxide	13463-67-7	3 - 7	*
Feldspar	68476-25-5	1 - 5	*
Texanol	25265-77-4	1 - 5	*
Ethylene Glycol	107-21-1	1 - 5	*
Crystalline Silica	14808-60-7	0.1 - 1	*
3-iodo-2-propynyl butyl carbamate	55406-53-6	0.1 - 1	*
Ammonium Hydroxide	1336-21-6	0.1 - 1	*
Sodium nitrite	7632-00-0	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contactRinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.
Consult a physician.Skin ContactWash skin with soap and water.InhalationRemove to fresh air.IngestionClean mouth with water and drink afterwards plenty of water.Most important symptoms and effects, both acute and delayedSymptomsNo information available.Indication of any immediate medicate medicate medicate and special treatment neededNote to physiciansTreat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions, protective equipment and emergency procedures		
Personal precautions	Ensure adequate ventilation, especially in confined areas.	
Environmental precautions		
Environmental precautions	See Section 12 for additional Ecological Information.	
Methods and material for containment and cleaning up		
Methods for containment	Prevent further leakage or spillage if safe to do so.	
Methods for cleaning up	Use personal protective equipment as required. Dam up. Cover liquid spill with sand, earth or other non-combustible absorbent material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly.	

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
13463-67-7		TWA: 5 mg/m ³ respirable fraction	TWA: 2.4 mg/m ³ CIB 63 fine
			TWA: 0.3 mg/m ³ CIB 63 ultrafine,
			including engineered nanoscale
Ethylene Glycol	STEL: 50 ppm vapor fraction	(vacated) Ceiling: 50 ppm	-
107-21-1	STEL: 10 mg/m ³ inhalable	(vacated) Ceiling: 125 mg/m ³	
	particulate matter, aerosol only		
	TWA: 25 ppm vapor fraction		
Crystalline Silica	TWA: 0.025 mg/m ³ respirable	TWA: 50 μg/m ³ TWA: 50 μg/m ³	IDLH: 50 mg/m ³ respirable dust

14808-60-7	particulate matter	excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³	TWA: 0.05 mg/m³ re	espirable dust
		respirable dust : (250)/(%SiO2 + 5) mppcf TWA respirable fraction : (10)/(%SiO2 + 2) mg/m ³ TWA respirable fraction		

NIOSH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Showers Eyewash stations Ventilation systems.	
ich as personal protective equipment	
No special technical protective measures are necessary.	

Skin and body protection No special technical protective measures are necessary.

Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved
	respiratory protection should be worn. Positive-pressure supplied air respirators may be
	required for high airborne contaminant concentrations. Respiratory protection must be
	provided in accordance with current local regulations.

```
General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.
```

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Color	Liquid No information available No information available	Odor Odor threshold	No information available No information available
Property pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density Specific Gravity Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity	Values 9.3 ± 0.2 No information available>= 100 °C / 212 °F> 94 °C / > 201 °FNo information availableNo information available	<u>Remarks • Method</u>	

Explosive properties	No information available
Oxidizing properties	No information available
Other Information	
Softening point	No information available
Molecular weight	No information available
Liquid Density	9.31 lbs/gal
Bulk density	No information available
Percent solids by weight	41.8%
Percent volatile by weight	4.4%
Percent solids by volume	34.9%
Actual VOC (lbs/gal)	0.4
Actual VOC (grams/liter)	49.5
EPA VOC (lbs/gal)	1
EPA VOC (grams/liter)	124.4
EPA VOC (lb/gal solids)	1.2

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin Contact	No data available.
Ingestion	No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Texanol 25265-77-4	= 3200 mg/kg (Rat)	> 15200 mg/kg (Rat)	> 3.55 mg/L (Rat)6 h
Ethylene Glycol 107-21-1	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat)= 9530 µL/kg (Rabbit)	-
Crystalline Silica 14808-60-7	> 22,500 mg/kg (Rat)	-	-

3-iodo-2-propynyl butyl carbamate 55406-53-6	= 1470 mg/kg (Rat)	> 2000 mg/kg (Rat)	= 0.63 mg/L (Rat) 4 h = 0.67 mg/L (Rat) 4 h = 0.99 mg/L (Rat) 4 h
Ammonium Hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-
Sodium nitrite 7632-00-0	= 85 mg/kg (Rat)	-	= 5.5 mg/L (Rat)4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure_

Sensitization Germ cell mutagenicity Carcinogenicity	No information No information No information	n available.		
Chemical name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	Х
Crystalline Silica 14808-60-7	A2	Group 1	Known	Х
Sodium nitrite 7632-00-0	-	Group 2A	-	Х
A2 - Suspected Human C	ency for Research on Cancer	50 /		

Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans NTP (National Toxicology Program) Known - Known Carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure Target organ effects

Aspiration hazard

No information available. Central nervous system, Eyes, Lungs, Respiratory system, Skin. No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

12.11% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Texanol	18.4: 72 h Pseudokirchneriella	30: 96 h Pimephales promelas mg/L	95: 96 h Daphnia magna mg/L LC50
25265-77-4	subcapitata mg/L EC50	LC50	
Ethylene Glycol	6500 - 13000: 96 h	41000: 96 h Oncorhynchus mykiss	46300: 48 h Daphnia magna mg/L
107-21-1	Pseudokirchneriella subcapitata	mg/L LC50 14 - 18: 96 h	EC50
	mg/L EC50	Oncorhynchus mykiss mL/L LC50	
		static 27540: 96 h Lepomis	
		macrochirus mg/L LC50 static	
		40000 - 60000: 96 h Pimephales	
		promelas mg/L LC50 static 40761:	
		96 h Oncorhynchus mykiss mg/L	
		LC50 static 16000: 96 h Poecilia	
		reticulata mg/L LC50 static	
3-iodo-2-propynyl butyl carbamate	-	0.14 - 0.32: 96 h Lepomis	-
55406-53-6		macrochirus mg/L LC50	

	flow-through 0.05 - 0.089: 96 h Oncorhynchus mykiss mg/L LC50 0.18 - 0.23: 96 h Pimephales promelas mg/L LC50 flow-through 0.049 - 0.079: 96 h Oncorhynchus	
Ammonium Hydroxide 1336-21-6	- mykiss mg/L LC50 flow-through - 8.2: 96 h Pimephales promelas mg/L LC50	0.66: 48 h water flea mg/L EC50 0.66: 48 h Daphnia pulex mg/L EC50
Sodium nitrite 7632-00-0	- 0.19: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.65 - 1: 9 h Oncorhynchus mykiss mg/L LC50 static 0.092 - 0.13: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.4 - 0.6: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 2.3: 96 h Pimephales promelas mg/L LC50 flow-through 20: 96 h Pimephales promelas mg/	

Persistence and degradability No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Texanol	3.47
25265-77-4	
Ethylene Glycol	-1.93
107-21-1	
Sodium nitrite	-3.7
7632-00-0	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods	
Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
US EPA Waste Number	U161

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Ammonium Hydroxide	Toxic
1336-21-6	Corrosive
Sodium nitrite	Toxic
7632-00-0	Ignitable
	Reactive

14. TRANSPORT INFORMATION

DOT

Not regulated

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies [*]

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %	
Feldspar	1.0	
Ethylene Glycol	1.0	

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ammonium Hydroxide 1336-21-6	1000 lb	-	-	Х
Sodium nitrite 7632-00-0	100 lb	-	-	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ethylene Glycol	5000 lb	-	RQ 5000 lb final RQ
107-21-1			RQ 2270 kg final RQ
Ammonium Hydroxide	1000 lb	-	RQ 1000 lb final RQ
1336-21-6			RQ 454 kg final RQ
Sodium nitrite	100 lb	-	RQ 100 lb final RQ
7632-00-0			RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65	
Titanium dioxide - 13463-67-7	Carcinogen	
Ethylene Glycol - 107-21-1	Developmental	
Crystalline Silica - 14808-60-7	Carcinogen	
Lead - 7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive	
Methyl Isobutyl Ketone - 108-10-1	Carcinogen Developmental	

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Titanium dioxide	Х	X
13463-67-7		
Feldspar	Х	-
68476-25-5		
Ethylene Glycol	Х	X
107-21-1		
Crystalline Silica	Х	X
14808-60-7		
Ammonium Hydroxide	X	X
1336-21-6		

Chemical name	Pennsylvania
Titanium dioxide	Х
13463-67-7	
Feldspar	Х
68476-25-5	
Ethylene Glycol	Х
107-21-1	

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present individually at 1% by weight, or greater):

Chemical name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Ethylene Glycol	1.91%	0.18
107-21-1		

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 1	Flammability 1	Instability 0	Physical and chemical properties -
<u>HMIS</u> Chronic Hazard Star Le	Health hazards 1 * egend * = Chronic	Flammability 1 Health Hazard	Physical hazards 0	Personal protection X

15-Jun-2020

Revision Date Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet