

## 1. IDENTIFICATION

**Product identifier**

**Product Name** MultiPUR - Multicoat 2K Poly Gloss

**Other means of identification**

**Product Code** CG0259-100  
**UN/ID no** UN1263  
**SKU(s)** CG0259-100, CG0259-500

**Recommended use of the chemical and restrictions on use**

**Recommended Use** No information available.  
**Uses advised against** No information available

**Details of the supplier of the safety data sheet**

**Manufacturer Address**

Diamond Vogel  
 1020 Albany Place SE  
 Orange City, IA 51041  
 Phone: (712) 737-4993  
 Fax: (712) - 737-4997

**Emergency telephone number**

**Emergency Telephone** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

**Classification**

**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

**Emergency Overview**

**Danger**

**Hazard statements**

Causes serious eye irritation  
 May cause an allergic skin reaction  
 May cause cancer  
 Suspected of damaging fertility or the unborn child  
 May cause respiratory irritation. May cause drowsiness or dizziness  
 Highly flammable liquid and vapor

**Appearance** No information available**Physical state** Liquid**Odor** No information available**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation or rash occurs: Get medical advice/attention  
 Wash contaminated clothing before reuse  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other Information**

- Causes mild skin irritation
  - Harmful to aquatic life
- Unknown acute toxicity                      0% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Butyl Acetate	123-86-4	30 - 60	*
Xylene	1330-20-7	5 - 10	*
Methyl Isobutyl Ketone	108-10-1	5 - 10	*
Acetone	67-64-1	3 - 7	*
Nitrocellulose	9004-70-0	1 - 5	*
Ethyl Benzene	100-41-4	1 - 5	*

Isopropyl Alcohol	67-63-0	1 - 5	*
Methyl methacrylate	80-62-6	0.1 - 1	*
Toluene	108-88-3	0.1 - 1	*
2-hydroxyethyl methacrylate	868-77-9	0.1 - 1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
<b>Skin Contact</b>	Call a physician immediately.
<b>Inhalation</b>	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately. If breathing is difficult, give oxygen.
<b>Ingestion</b>	Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

##### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

##### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** CAUTION: Use of water spray when fighting fire may be inefficient.

##### Specific hazards arising from the chemical

Extremely flammable.

##### Explosion data

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use personal protective equipment as required. Remove all sources of ignition.

##### Environmental precautions

**Environmental precautions** Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

##### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up with inert absorbent material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Strong acids. Strong oxidizing agents. Chlorinated compounds. Acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Butyl Acetate 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m <sup>3</sup> (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Methyl Isobutyl Ketone 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m <sup>3</sup> (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m <sup>3</sup>	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 300 mg/m <sup>3</sup>
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
Isopropyl Alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
Methyl methacrylate 80-62-6	STEL: 100 ppm TWA: 50 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 410 mg/m <sup>3</sup>	IDLH: 1000 ppm TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>

Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
---------------------	-------------	--	---

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Appropriate engineering controls

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** No special technical protective measures are necessary.

**Skin and body protection** No special technical protective measures are necessary.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid	<b>Odor</b>	No information available
<b>Appearance</b>	No information available	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	No information available	
<b>Melting point / freezing point</b>	No information available	
<b>Boiling point / boiling range</b>	>= 56 °C / 133 °F	
<b>Flash point</b>	-12 °C / 10 °F	
<b>Evaporation rate</b>	No information available	
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	No information available	
<b>Lower flammability limit:</b>	No information available	
<b>Vapor pressure</b>	No information available	
<b>Vapor density</b>	No information available	
<b>Specific Gravity</b>	0.93	
<b>Water solubility</b>	No information available	
<b>Solubility in other solvents</b>	No information available	
<b>Partition coefficient</b>	No information available	
<b>Autoignition temperature</b>	No information available	
<b>Decomposition temperature</b>	No information available	
<b>Kinematic viscosity</b>	No information available	
<b>Dynamic viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	

### Other Information

Softening point	No information available
Molecular weight	No information available
Liquid Density	7.75 lbs/gal
Bulk density	No information available
Percent solids by weight	25.2%
Percent volatile by weight	69.5%
Percent solids by volume	19.3%
Actual VOC (lbs/gal)	5.4
Actual VOC (grams/liter)	645.7
EPA VOC (lbs/gal)	5.7
EPA VOC (grams/liter)	688.5
EPA VOC (lb/gal solids)	27.9

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Strong acids. Strong oxidizing agents. Chlorinated compounds. Acids.

### Hazardous decomposition products

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	No data available
<b>Inhalation</b>	No data available.
<b>Eye contact</b>	No data available.
<b>Skin Contact</b>	No data available.
<b>Ingestion</b>	No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Butyl Acetate 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
Xylene 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit ) > 1700 mg/kg ( Rabbit )	= 5000 ppm ( Rat ) 4 h = 29.08 mg/L ( Rat ) 4 h
Methyl Isobutyl Ketone 108-10-1	= 2080 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 8.2 mg/L ( Rat ) 4 h
Acetone 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
Nitrocellulose 9004-70-0	> 5 g/kg ( Rat )	-	-
Ethyl Benzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
Isopropyl Alcohol 67-63-0	= 1870 mg/kg ( Rat )	= 4059 mg/kg ( Rabbit )	= 72600 mg/m <sup>3</sup> ( Rat ) 4 h

Methyl methacrylate 80-62-6	8420 - 10000 mg/kg ( Rat ) = 7872 mg/kg ( Rat )	5000 - 7500 mg/kg ( Rabbit ) > 5 g/kg ( Rabbit )	= 7093 ppm ( Rat ) 4 h
Toluene 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
2-hydroxyethyl methacrylate 868-77-9	= 5050 mg/kg ( Rat )	> 3000 mg/kg ( Rabbit )	-

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** No information available.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Methyl Isobutyl Ketone 108-10-1	A3	Group 2B	-	X
Nitrocellulose 9004-70-0	-	Group 2A	-	X
Ethyl Benzene 100-41-4	A3	Group 2B	-	X
Isopropyl Alcohol 67-63-0	-	Group 3	-	X
Methyl methacrylate 80-62-6	-	Group 3	-	-
Toluene 108-88-3	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Reproductive toxicity** Product is or contains a chemical which is a known or suspected reproductive hazard.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic toxicity**

Contains a known or suspected reproductive toxin. Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. May cause adverse liver effects.

**Target organ effects** Central nervous system, Eyes, kidney, liver, Respiratory system, Skin.

**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Harmful to aquatic life

2.66% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Butyl Acetate 123-86-4	674.7: 72 h <i>Desmodesmus</i> <i>subspicatus</i> mg/L EC50	100: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 17 - 19: 96 h <i>Pimephales promelas</i> mg/L LC50	72.8: 24 h <i>Daphnia magna</i> mg/L EC50

		flow-through 62: 96 h <i>Leuciscus idus</i> mg/L LC50 static	
Xylene 1330-20-7	-	13.4: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 13.5 - 17.3: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 23.53 - 29.97: 96 h <i>Pimephales promelas</i> mg/L LC50 static 2.661 - 4.093: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 780: 96 h <i>Cyprinus carpio</i> mg/L LC50 semi-static 780: 96 h <i>Cyprinus carpio</i> mg/L LC50 30.26 - 40.75: 96 h <i>Poecilia reticulata</i> mg/L LC50 static 19: 96 h <i>Lepomis macrochirus</i> mg/L LC50 7.711 - 9.591: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 13.1 - 16.5: 96 h <i>Lepomis macrochirus</i> mg/L LC50 flow-through	3.82: 48 h water flea mg/L EC50 0.6: 48 h <i>Gammarus lacustris</i> mg/L LC50
Methyl Isobutyl Ketone 108-10-1	400: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50	496 - 514: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through	170: 48 h <i>Daphnia magna</i> mg/L EC50
Acetone 67-64-1	-	4.74 - 6.33: 96 h <i>Oncorhynchus mykiss</i> mL/L LC50 6210 - 8120: 96 h <i>Pimephales promelas</i> mg/L LC50 static 8300: 96 h <i>Lepomis macrochirus</i> mg/L LC50	10294 - 17704: 48 h <i>Daphnia magna</i> mg/L EC50 Static 12600 - 12700: 48 h <i>Daphnia magna</i> mg/L EC50
Ethyl Benzene 100-41-4	4.6: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 2.6 - 11.3: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 static 1.7 - 7.6: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 static 438: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50	11.0 - 18.0: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 7.55 - 11: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 4.2: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 semi-static 32: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 9.6: 96 h <i>Poecilia reticulata</i> mg/L LC50 static 9.1 - 15.6: 96 h <i>Pimephales promelas</i> mg/L LC50 static	1.8 - 2.4: 48 h <i>Daphnia magna</i> mg/L EC50
Isopropyl Alcohol 67-63-0	1000: 96 h <i>Desmodesmus subspicatus</i> mg/L EC50 1000: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	9640: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 11130: 96 h <i>Pimephales promelas</i> mg/L LC50 static 1400000: 96 h <i>Lepomis macrochirus</i> µg/L LC50	13299: 48 h <i>Daphnia magna</i> mg/L EC50
Methyl methacrylate 80-62-6	170: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50	125.5 - 190.7: 96 h <i>Pimephales promelas</i> mg/L LC50 static 243 - 275: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 170 - 206: 96 h <i>Lepomis macrochirus</i> mg/L LC50 flow-through 153.9 - 341.8: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 326.4 - 426.9: 96 h <i>Poecilia reticulata</i> mg/L LC50 static 79: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 79: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through	69: 48 h <i>Daphnia magna</i> mg/L EC50
Toluene 108-88-3	433: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 12.5: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 static	15.22 - 19.05: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 12.6: 96 h <i>Pimephales promelas</i> mg/L LC50 static 28.2: 96 h <i>Poecilia reticulata</i> mg/L LC50 semi-static 54: 96 h <i>Oryzias latipes</i> mg/L LC50 static 5.89 - 7.81: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through 11.0 - 15.0: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 50.87 - 70.34: 96 h <i>Poecilia reticulata</i> mg/L LC50 static 14.1 - 17.16: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 5.8: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 semi-static	5.46 - 9.83: 48 h <i>Daphnia magna</i> mg/L EC50 Static 11.5: 48 h <i>Daphnia magna</i> mg/L EC50
2-hydroxyethyl methacrylate	-	227: 96 h <i>Pimephales promelas</i>	-



868-77-9		mg/L LC50 213 - 242: 96 h Pimephales promelas mg/L LC50 flow-through	
----------	--	--	--

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical name	Partition coefficient
Butyl Acetate 123-86-4	1.81
Xylene 1330-20-7	3.15
Methyl Isobutyl Ketone 108-10-1	1.19
Acetone 67-64-1	-0.24
Ethyl Benzene 100-41-4	3.2
Isopropyl Alcohol 67-63-0	0.05
Methyl methacrylate 80-62-6	0.7
Toluene 108-88-3	2.7
2-hydroxyethyl methacrylate 868-77-9	0.47

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging**

Do not reuse container.

**US EPA Waste Number**

D001 U161 U220 U239 U002 U019 U162 U055

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7	-	Included in waste stream: F039	-	U239
Methyl Isobutyl Ketone 108-10-1	-	Included in waste stream: F039	-	U161
Acetone 67-64-1	-	Included in waste stream: F039	-	U002
Ethyl Benzene 100-41-4	-	Included in waste stream: F039	-	-
Methyl methacrylate 80-62-6	U162	Included in waste stream: F039	-	U162
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	-	U220

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent	-

			filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	
--	--	--	---	--

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Butyl Acetate 123-86-4	Toxic
Xylene 1330-20-7	Toxic Ignitable
Acetone 67-64-1	Ignitable
Nitrocellulose 9004-70-0	Ignitable Reactive
Ethyl Benzene 100-41-4	Toxic Ignitable
Isopropyl Alcohol 67-63-0	Toxic Ignitable
Methyl methacrylate 80-62-6	Toxic Ignitable
Toluene 108-88-3	Toxic Ignitable

#### 14. TRANSPORT INFORMATION

##### DOT

**UN/ID no** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Reportable Quantity (RQ)** (Ethyl Benzene: RQ (kg)= 454.00, Toluene: RQ (kg)= 0.454, Butyl Acetate: RQ (kg)= 2270.00, Xylene: RQ (kg)= 45.40)  
**Special Provisions** 149, B52, IB2, T4, TP1, TP8, TP28  
**Description** UN1263, Paint, 3, II  
**Emergency Response Guide Number** 128

##### TDG

**UN/ID no** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Special Provisions** 59, 83  
**Description** UN1263, Paint, 3, II

##### MEX

**UN/ID no** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Special Provisions** 163  
**Packing Group** II  
**Description** UN1263, Paint, 3, II

**ICAO (air)**

UN/ID no	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Special Provisions	A3, A72
Description	UN1263, Paint, 3, II

**IATA**

UN Number	UN1263
Proper shipping name	Paint
Transport hazard class(es)	3
Packing Group	II
ERG Code	3L
Special Provisions	A3, A72
Description	UN1263, Paint, 3, II

**IMDG**

UN Number	UN1263
Transport hazard class(es)	3
Packing Group	II
EmS-No	F-E, S-E
Special Provisions	163
Description	UN1263, Paint, 3, II, (-12°C c.c.)

**RID**

UN/ID no	UN1263
Proper shipping name	Paint
Transport hazard class(es)	3
Packing Group	II
Classification code	F1
Special Provisions	163, 640C, 650
Description	UN1263, Paint, 3, II
Labels	3

**ADR**

UN Number	UN1263
Proper shipping name	Paint
Transport hazard class(es)	3
Packing Group	II
Classification code	F1
Tunnel restriction code	(D/E)
Special Provisions	163, 640C, 650
Description	UN1263, Paint, 3, II, (D/E)
Labels	3

**ADN**

Proper shipping name	Paint
Transport hazard class(es)	3
Packing Group	II
Classification code	F1
Special Provisions	163, 640C, 650
Description	UN1263, Paint, 3, II
Hazard label(s)	3
Limited quantity (LQ)	5 L
Ventilation	VE01
Equipment Requirements	PP, EX, A

**15. REGULATORY INFORMATION****International Inventories**

TSCA	Complies
DSL/NDSL	Complies *

<b>EINECS/ELINCS</b>	Does not comply *
<b>ENCS</b>	Does not comply *
<b>IECSC</b>	Complies *
<b>KECL</b>	Complies *
<b>PICCS</b>	Complies *
<b>AICS</b>	Complies *

\* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

### US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Xylene	1.0
Methyl Isobutyl Ketone	1.0
Ethyl Benzene	0.1
Isopropyl Alcohol	1.0

#### SARA 311/312 Hazard Categories

<b>Acute health hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl Acetate 123-86-4	5000 lb	-	-	X
Xylene 1330-20-7	100 lb	-	-	X
Ethyl Benzene 100-41-4	1000 lb	X	X	X
Methyl methacrylate 80-62-6	1000 lb	-	-	X
Toluene 108-88-3	1000 lb	X	X	X

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Butyl Acetate 123-86-4	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Methyl Isobutyl Ketone 108-10-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethyl Benzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Methyl methacrylate 80-62-6	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Toluene 108-88-3	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Methyl Isobutyl Ketone - 108-10-1	Carcinogen Developmental
Ethyl Benzene - 100-41-4	Carcinogen
Toluene - 108-88-3	Developmental
Cumene - 98-82-8	Carcinogen
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen Developmental Male Reproductive
Methyl Styrene - 98-83-9	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts
Butyl Acetate 123-86-4	X	X
Xylene 1330-20-7	X	X
Methyl Isobutyl Ketone 108-10-1	X	X
Acetone 67-64-1	X	X
Nitrocellulose 9004-70-0	X	X
Ethyl Benzene 100-41-4	X	X
Isopropyl Alcohol 67-63-0	X	X
Methyl methacrylate 80-62-6	X	X
Toluene 108-88-3	X	X

Chemical name	Pennsylvania
Butyl Acetate 123-86-4	X
Xylene 1330-20-7	X
Methyl Isobutyl Ketone 108-10-1	X
Acetone 67-64-1	X
Nitrocellulose 9004-70-0	X
Ethyl Benzene 100-41-4	X
Isopropyl Alcohol 67-63-0	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**Hazardous air pollutants (HAPS) content**

