

## SAFETY DATA SHEET

Revision Date 01-Dec-2022 Version 5

## 1. IDENTIFICATION

**Product identifier** 

Product Name PermAcryl Interior Latex Eggshell Mid Tone Base

Other means of identification

Product Code DE-1532 SKU(s) None

Recommended use of the chemical and restrictions on use
Recommended Use
Uses advised against
No information available

Details of the supplier of the safety data sheet

**Manufacturer Address** 

Diamond Vogel 1020 Albany Place SE Orange City, IA 51041 Phone: (712) 737-4993 Fax: (712) 737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

### Classification

**OSHA Regulatory Status** 

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity Category 1A

**Emergency Overview** 

#### Danger

#### Hazard statements

May cause cancer



Appearance No information available

Physical state Liquid

Odor No information available

## **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

#### **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

#### Other Information

Very toxic to aquatic life with long lasting effects

Unknown acute toxicity 10.97% of the mixture consists of ingredient(s) of unknown toxicity

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Feldspar	68476-25-5	7 - 13	*
Titanium dioxide	13463-67-7	5 - 10	*
Kaolin	1332-58-7	1 - 5	*
Crystalline Silica	14808-60-7	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

## **Description of first aid measures**

**Eye contact** Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

**Skin Contact** Wash skin with soap and water.

**Inhalation** Remove to fresh air.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

#### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

## Indication of any immediate medical attention and special treatment needed

## 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

No information available.

#### **Explosion data**

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation, especially in confined areas.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use personal protective equipment as required. Dam up. Cover liquid spill with sand, earth

or other non-combustible absorbent material. Take up mechanically, placing in appropriate

containers for disposal. Clean contaminated surface thoroughly.

## 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

**Incompatible materials**None known based on information supplied.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Titanium dioxide	TWA: 0.2 mg/m³ nanoscale	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7	respirable particulate matter	TWA: 5 mg/m³ respirable fraction	TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine
	TWA: 2.5 mg/m³ finescale		TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine,
	respirable particulate matter		including engineered nanoscale
Kaolin	TWA: 2 mg/m³ particulate matter	TWA: 15 mg/m³ total dust	TWA: 10 mg/m³ total dust
1332-58-7	containing no asbestos and <1%	TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m³ respirable dust
	crystalline silica, respirable	(vacated) TWA: 10 mg/m <sup>3</sup> total dust	
	particulate matter	(vacated) TWA: 5 mg/m³ respirable	
		fraction	
Crystalline Silica	TWA: 0.025 mg/m³ respirable	TWA: 50 μg/m³ TWA: 50 μg/m³	IDLH: 50 mg/m3 respirable dust
14808-60-7	particulate matter	excludes construction work,	TWA: 0.05 mg/m³ respirable dust
		agricultural operations, and	
		exposures that result from the	
		processing of sorptive clays	
		(vacated) TWA: 0.1 mg/m <sup>3</sup>	
		respirable dust	
		: (250)/(%SiO2 + 5) mppcf TWA	
		respirable fraction	
		: (10)/(%SiO2 + 2) mg/m³ TWA	
		respirable fraction	

NIOSH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

\_\_\_\_\_

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face protection** No special technical protective measures are necessary.

**Skin and body protection**No special technical protective measures are necessary.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Remarks • Method

provided in accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Liquid

AppearanceNo information availableOdorNo information availableColorNo information availableOdor thresholdNo information available

Property Values

**oH** 8.5-9.5

Melting point / freezing pointNo information availableBoiling point / boiling range>= 72 °C / 162 °FFlash point> 94 °C / > 201 °FEvaporation rateNo information availableFlammability (solid, gas)No information available

Flammability Limit in Air

Upper flammability limit:No information availableLower flammability limit:No information availableVapor pressureNo information availableVapor densityNo information available

Specific Gravity 1.23

Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available **Explosive properties** No information available Oxidizing properties No information available

**Other Information** 

Softening point No information available Molecular weight No information available

Liquid Density 10.26 lbs/gal

Bulk density No information available

Percent solids by weight 46.5% Percent volatile by weight 1.4% Percent solids by volume 34.2%

## DE-1532 PermAcryl Interior Latex Eggshell Mid Tone Base

 Actual VOC (lbs/gal)
 0.1

 Actual VOC (grams/liter)
 16.8

 EPA VOC (lbs/gal)
 0.4

 EPA VOC (grams/liter)
 47

 EPA VOC (lb/gal solids)
 0.4

## 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

## Possibility of hazardous reactions

None under normal processing.

#### Conditions to avoid

Extremes of temperature and direct sunlight.

#### **Incompatible materials**

None known based on information supplied.

#### **Hazardous decomposition products**

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

Product Information No data available

**Inhalation** No data available.

**Eye contact** No data available.

**Skin Contact** No data available.

**Ingestion** No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat) 4 h
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
Crystalline Silica 14808-60-7	> 22,500 mg/kg (Rat)	-	-

## Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium dioxide	A3	Group 2B	-	X
13463-67-7		-		
Crystalline Silica	A2	Group 1	Known	X

# DE-1532 PermAcryl Interior Latex Eggshell Mid Tone Base

14808-60-7

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Target organ effects Eyes, Lungs, Respiratory system.

Aspiration hazard No information available.

#### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Very toxic to aquatic life with long lasting effects

23.97% of the mixture consists of components(s) of unknown hazards to the aquatic environment

#### Persistence and degradability

No information available.

#### Bioaccumulation

No information available.

Other adverse effects No information available

## 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

## 14. TRANSPORT INFORMATION

**DOT** Not regulated

TDG Not regulated

MEX Not regulated

ICAO (air) Not regulated

IATA Not regulated

IMDG Not regulated

# DE-1532 PermAcryl Interior Latex Eggshell Mid Tone Base

RID Not regulated

ADR Not regulated

ADN Not regulated

## 15. REGULATORY INFORMATION

**International Inventories** 

TSCA Complies
DSL/NDSL Complies \*

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

## **US Federal Regulations**

## **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Feldspar - 68476-25-5	1.0

#### SARA 311/312 Hazard Categories

Acute health hazard No
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

## **US State Regulations**

## **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen
Ethylene Glycol - 107-21-1	Developmental
Acetaldehyde - 75-07-0	Carcinogen
Lead - 7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive
Mercury - 7439-97-6	Developmental
Nickel - 7440-02-0	Carcinogen
Cadmium - 7440-43-9	Carcinogen Developmental Male Reproductive
Cobalt - 7440-48-4	Carcinogen
Lead Chromate - 7758-97-6	Carcinogen Developmental Female Reproductive Male Reproductive

### **U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts
Feldspar	X	-
68476-25-5		
Titanium dioxide	X	X

<sup>\*</sup> This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

\_\_\_\_\_

13463-67-7		
Kaolin	X	X
1332-58-7		
Crystalline Silica 14808-60-7	X	X
14808-60-7		
Ethanolamine	X	X
141-43-5		

Chemical name	Pennsylvania
Feldspar 68476-25-5	X
Titanium dioxide 13463-67-7	X
Kaolin 1332-58-7	X
Crystalline Silica 14808-60-7	X

**U.S. EPA Label Information** 

EPA Pesticide Registration Number Not applicable

This product contains no Hazardous Air Pollutants individually at 1% by weight, or greater.

## 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 1 Instability 0 Physical and chemical

properties -

Health hazards 1 \* Flammability 1 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend \*= Chronic Health Hazard

Revision Date 01-Dec-2022

**Revision Note** 

No information available

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

**End of Safety Data Sheet**