

## 1. IDENTIFICATION

**Product identifier**

**Product Name** Vantage Plus Interior Latex Flat Enamel Deep Base

**Other means of identification**

**Product Code** DF-1643

**SKU(s)** None

**Recommended use of the chemical and restrictions on use**

**Recommended Use** No information available.

**Uses advised against** No information available

**Details of the supplier of the safety data sheet**

**Manufacturer Address**

Diamond Vogel  
1020 Albany Place SE  
Orange City, IA 51041  
Phone: (712) 737-4993  
Fax: (712) 737-4997

**Emergency telephone number**

**Emergency Telephone** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

**Classification**

**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 1A
-----------------	-------------

**Emergency Overview**

**Danger**

**Hazard statements**

May cause cancer



**Appearance** No information available

**Physical state** Liquid

**Odor** No information available

**Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other Information**

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%	Trade Secret
Calcium carbonate	1317-65-3	10 - 30	*
Kaolin	1332-58-7	3 - 7	*
Titanium dioxide	13463-67-7	3 - 7	*
Ethylene Glycol	107-21-1	1 - 5	*
Crystalline Silica	14808-60-7	0.1 - 1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****Description of first aid measures**

<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
<b>Skin Contact</b>	Wash skin with soap and water.
<b>Inhalation</b>	Remove to fresh air.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water.

**Most important symptoms and effects, both acute and delayed****Symptoms** No information available.**Indication of any immediate medical attention and special treatment needed****Note to physicians** Treat symptomatically.**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** CAUTION: Use of water spray when fighting fire may be inefficient.**Specific hazards arising from the chemical**

No information available.

**Explosion data****Sensitivity to Mechanical Impact** None.**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation, especially in confined areas.

Environmental precautions

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Use personal protective equipment as required. Dam up. Cover liquid spill with sand, earth or other non-combustible absorbent material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly.

**7. HANDLING AND STORAGE**

Precautions for safe handling

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

**Incompatible materials** None known based on information supplied.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Control parameters

**Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Calcium carbonate 1317-65-3	TWA: 10 mg/m <sup>3</sup> inhalable particles TWA: 3 mg/m <sup>3</sup> respirable particles	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Kaolin 1332-58-7	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	IDLH: 5000 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine, including engineered nanoscale
Ethylene Glycol 107-21-1	STEL: 50 ppm vapor fraction STEL: 10 mg/m <sup>3</sup> inhalable particulate matter, aerosol only TWA: 25 ppm vapor fraction	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m <sup>3</sup>	-
Crystalline Silica 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust

		respirable fraction : (10)/(100SiO2 + 2) mg/m <sup>3</sup> TWA respirable fraction	
--	--	--	--

NIOSH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** No special technical protective measures are necessary.

**Skin and body protection** No special technical protective measures are necessary.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid	<b>Odor</b>	No information available
<b>Appearance</b>	No information available	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	8.8±0.2	
Melting point / freezing point	No information available	
Boiling point / boiling range	>= 100 °C / 212 °F	
Flash point	> 94 °C / > 201 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	1.37	
Water solubility	No information available	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

**Other Information**

**Softening point** No information available

<b>Molecular weight</b>	No information available
<b>Liquid Density</b>	11.42 lbs/gal
<b>Bulk density</b>	No information available
<b>Percent solids by weight</b>	52.2%
<b>Percent volatile by weight</b>	1.1%
<b>Percent solids by volume</b>	34.5%
<b>Actual VOC (lbs/gal)</b>	0.1
<b>Actual VOC (grams/liter)</b>	15.7
<b>EPA VOC (lbs/gal)</b>	0.4
<b>EPA VOC (grams/liter)</b>	43.6
<b>EPA VOC (lb/gal solids)</b>	0.4

**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Extremes of temperature and direct sunlight.

**Incompatible materials**

None known based on information supplied.

**Hazardous decomposition products**

None known based on information supplied.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

<b>Product Information</b>	No data available
<b>Inhalation</b>	No data available.
<b>Eye contact</b>	No data available.
<b>Skin Contact</b>	No data available.
<b>Ingestion</b>	No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Calcium carbonate 1317-65-3	= 6450 mg/kg (Rat)	-	-
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg ( Rat )	-
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Ethylene Glycol 107-21-1	= 4700 mg/kg ( Rat )	= 10600 mg/kg ( Rat ) = 9530 µL/kg ( Rabbit )	-
Crystalline Silica 14808-60-7	> 22,500 mg/kg (Rat)	-	-

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** No information available.

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Crystalline Silica 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)  
 A2 - Suspected Human Carcinogen  
 IARC (International Agency for Research on Cancer)  
 Group 1 - Carcinogenic to Humans  
 Group 2B - Possibly Carcinogenic to Humans  
 Group 3 - Not classifiable as a human carcinogen  
 NTP (National Toxicology Program)  
 Known - Known Carcinogen  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
 X - Present

**Reproductive toxicity** No information available.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Target organ effects** Central nervous system, Eyes, Lungs, Respiratory system, Skin.  
**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document mg/kg

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

39.61% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Ethylene Glycol 107-21-1	6500 - 13000: 96 h Pseudokirchneriella subcapitata mg/L EC50	41000: 96 h Oncorhynchus mykiss mg/L LC50 14 - 18: 96 h Oncorhynchus mykiss mL/L LC50 static 27540: 96 h Lepomis macrochirus mg/L LC50 static 40000 - 60000: 96 h Pimephales promelas mg/L LC50 static 40761: 96 h Oncorhynchus mykiss mg/L LC50 static 16000: 96 h Poecilia reticulata mg/L LC50 static	46300: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical name	Partition coefficient
Ethylene Glycol 107-21-1	-1.93

**Other adverse effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

**14. TRANSPORT INFORMATION**

**DOT** Not regulated

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Complies  
**DSL/NDSL** Complies \*

\* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Ethylene Glycol - 107-21-1	1.0

**SARA 311/312 Hazard Categories**

**Acute health hazard** No  
**Chronic Health Hazard** No  
**Fire hazard** No  
**Sudden release of pressure hazard** No  
**Reactive Hazard** No

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ethylene Glycol 107-21-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethylene Glycol - 107-21-1	Developmental
Crystalline Silica - 14808-60-7	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts
Calcium carbonate 1317-65-3	X	X
Kaolin 1332-58-7	X	X
Titanium dioxide 13463-67-7	X	X
Ethylene Glycol 107-21-1	X	X
Crystalline Silica 14808-60-7	X	X

Chemical name	Pennsylvania
Calcium carbonate 1317-65-3	X
Kaolin 1332-58-7	X
Titanium dioxide 13463-67-7	X
Ethylene Glycol 107-21-1	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**Hazardous air pollutants (HAPS) content**

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present individually at 1% by weight, or greater):

Chemical name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Ethylene Glycol 107-21-1	1.05%	0.12

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

**NFPA** Health hazards 1 Flammability 1 Instability 0 Physical and chemical properties -  
**HMIS** Health hazards 1 \* Flammability 1 Physical hazards 0 Personal protection X  
*Chronic Hazard Star Legend \* = Chronic Health Hazard*

Revision Date 28-Aug-2020

Revision Note  
 No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet