

PRODUCT DATA SHEET

Product Codes

Stain CI-0760

Description

Interior Penetrating Wood Stain

Features

- Color fast and non-bleeding
- Fast dry yet has adequate open-time to apply and wipe
- Direct-to-wood solvent based stains formulated for shop application in a manufacturing operation
- Unlimited number of colors are possible using the Easy Color Stain when tinting with approved 844 Colorant

Uses

Interior wood surfaces, kitchen cabinets, restaurant and store fixtures, furniture and fine architectural woodwork

Physical Properties

Weight	7.3 lb/gal
Solids Weight	5.58%
Solids Volume	3.65%
Theoretical Coverage	250 to 375 sq. ft./gal
Flash Point	110°F
VOC	826 g/L
HAPS	0.38 lbs of HAPS/lbs of solids

Surface Preparation

New Work:

Sand raw wood to desired smoothness using successively finer grades of sandpaper. Avoid polishing maple and birch with excessively fine sandpaper. Wood should be clean and dust free, with moisture content of 6 to 8% prior to finishing. Proper sanding and preparation of substrate is critical to achieving consistent results.

Stain Precautions:

Rags or waste soaked with stain may spontaneously catch fire if improperly discarded. Immediately after use, place rags in a sealed, water filled, metal container.

Sealer:

Easy Color Stain may be top coated with most clear coatings, including lacquer, conversion varnish, and most two-component systems. When using water base or exotic coatings be sure stain is thoroughly dry before applying finish coats.

Application

Apply an even, wet coat of stain with a brush, cloth, or spray. Allow stain to penetrate and wet the wood fibers. Before stain begins to dry, wipe off excess stain with a soft cloth. If stain becomes tacky, re-wet surface with additional stain and wipe immediately. Note: Coarser sanding of raw wood will result in darker colors; finer sanding will result in lighter stain colors. Allow stain to dry thoroughly before top coating.

Clean-Up

Lacquer Thinner, Acetone, or any Ketone solvents

Dry Times at 68° F

Ready for Testing 14 days

Drying Conditions:

Conditions should NOT be below 65°F and 40% relative air humidity. Ideal conditions are 68°F to 77°F and 50 to 65% relative air humidity.

Storage

Storage Life	12 months in the closed, original container
Storage Temperature	60°F to 77°F in unopened container

Cautions

These products are designed for shop application and professional use only. Safety Data Sheets are available from your Diamond Vogel representative. Prior to use of this product, obtain and review the Safety Data Sheet for health and safety information. Read and observe all precautionary notices on container labels.

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Diamond Vogel does not control the applicaiton of its products, or the condition of the surfaces to which they are applied, Diamond Vogel liability will under no circumstances exceed replacement of the product. All technical information is subject to change without notice.