SAFETY DATA SHEET

Revision Date 20-Apr-2022

Diamond

'oqe

Version 8

1. IDENTIFICATION

Product identifier **Product Name**

V-766E White Vinyl

Other means of identification **Product Code** UN/ID no SKU(s)

IE-1601 UN1263 None

Recommended use of the chemical and restrictions on use **Recommended Use** No information available. Uses advised against No information available

Details of the supplier of the safety data sheet **Manufacturer Address Diamond Vogel** 1020 Albany Place SE Orange City, IA 51041 Phone: (712) 737-4993 Fax: (712) 737-4997

Emergency telephone number **Emergency Telephone**

Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Emergency Overview

Danger

Hazard statements Harmful if inhaled Causes skin irritation Causes serious eye irritation Suspected of causing cancer Suspected of damaging fertility or the unborn child May cause respiratory irritation. May cause drowsiness or dizziness May be fatal if swallowed and enters airways



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Use explosion-proof electrical/ventilating/lighting/equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention If skin irritation occurs: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- · May be harmful if swallowed
- · Toxic to aquatic life with long lasting effects
- · Toxic to aquatic life Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Toluene	108-88-3	15 - 40	*
Methyl Isobutyl Ketone	108-10-1	15 - 40	*
Titanium dioxide	13463-67-7	7 - 13	*
Diisodecyl Phthalate	68515-49-1	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin Contact	Wash skin with soap and water.
Inhalation	Remove to fresh air.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Most important symptoms and effe	cts, both acute and delayed
Symptoms	No information available.
Indication of any immediate medica	al attention and special treatment needed
Note to physicians	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical Flammable.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Methods for cleaning up	Soak up with inert absorbent material.		
Methods for containment	Prevent further leakage or spillage if safe to do so.		
Methods and material for containment and cleaning up			
Environmental precautions	Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.		
Environmental precautions			
Personal precautions	Remove all sources of ignition. Use personal protective equipment as required.		

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product.
Conditions for safe storage, including	ng any incompatibilities
Storage Conditions	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).
Incompatible materials	Strong oxidizing agents. Strong acids. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Toluene	TWA: 20 ppm	TWA: 200 ppm	IDLH: 500 ppm
108-88-3		(vacated) TWA: 100 ppm	TWA: 100 ppm
		(vacated) TWA: 375 mg/m ³	TWA: 375 mg/m ³
		(vacated) STEL: 150 ppm	STEL: 150 ppm
		(vacated) STEL: 560 mg/m ³	STEL: 560 mg/m ³
		Ceiling: 300 ppm	_
Methyl Isobutyl Ketone	STEL: 75 ppm	TWA: 100 ppm	IDLH: 500 ppm
108-10-1	TWA: 20 ppm	TWA: 410 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 205 mg/m ³
		(vacated) TWA: 205 mg/m ³	STEL: 75 ppm
		(vacated) STEL: 75 ppm	STEL: 300 mg/m ³
		(vacated) STEL: 300 mg/m ³	_
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
13463-67-7	-	TWA: 5 mg/m ³ respirable fraction	TWA: 2.4 mg/m ³ CIB 63 fine
			TWA: 0.3 mg/m ³ CIB 63 ultrafine,
			including engineered nanoscale

NIOSH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers
	Eyewash stations
	Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	No special technical protective measures are necessary.
Skin and body protection	No special technical protective measures are necessary.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid		
Appearance	No information available	Odor	No information available
Color	No information available	Odor threshold	No information available

Property_	Values	Remarks • Method
pH	No information available	<u>Homano motrou</u>
Melting point / freezing point	No information available	
Boiling point / boiling range	>= 80 °C / 176 °F	
Flash point	6 °C / 43 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	1.01	
Water solubility	No information available	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other Information		
Softening point	No information available	
Molecular weight	No information available	
Liquid Density	8.41 lbs/gal	
Bulk density	No information available	
Percent solids by weight	33.3%	
Percent volatile by weight	66.7%	
Percent solids by volume	19.4%	
Actual VOC (Ibs/gal)	5.6	
Actual VOC (grams/liter)	672.4	
EPA VOC (Ibs/gal)	5.6	
EPA VOC (grams/liter)	672.6	
EPA VOC (lb/gal solids)	29	

10. STABILITY AND REACTIVITY

Reactivity No data available

Chemical stability Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Strong acids. Chlorinated compounds.

Hazardous decomposition products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin Contact	No data available.
Ingestion	No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat)4 h
Methyl Isobutyl Ketone 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	2000 - 4000 ppm (Rat)4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Diisodecyl Phthalate 68515-49-1	> 60000 mg/kg (Rat)	= 16000 mg/kg(Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicity Carcinogenicity	No information available. No information available. No information available.			
Chemical name	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3	-	Group 3	-	-
Methyl Isobutyl Ketone 108-10-1	A3	Group 2B	-	X
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Group 2B - Possibly Caro Group 3 - Not classifiable NTP (National Toxicolo Known - Known Carcinoc	e as a human carcinogen gy Program) gen	cer) ration of the US Department of	f Labor)	
Reproductive toxicityProduct is or contains a chemical which is a known or suspected reproductive hazard.STOT - single exposureNo information available.STOT - repeated exposureNo information available.Chronic toxicityContains a known or suspected reproductive toxin. May cause adverse liver effects.Target organ effectsCentral nervous system, Eyes, kidney, liver, Lungs, Respiratory system, Skin.Aspiration hazardNo information available.			dverse liver effects.	

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

12.02% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea		

[1	1	
Toluene	433: 96 h Pseudokirchneriella	15.22 - 19.05: 96 h Pimephales	5.46 - 9.83: 48 h Daphnia magna
108-88-3	subcapitata mg/L EC50 12.5: 72 h	promelas mg/L LC50 flow-through	mg/L EC50 Static 11.5: 48 h
	Pseudokirchneriella subcapitata	12.6: 96 h Pimephales promelas	Daphnia magna mg/L EC50
	mg/L EC50 static	mg/L LC50 static 28.2: 96 h Poecilia	
	-	reticulata mg/L LC50 semi-static 54:	
		96 h Oryzias latipes mg/L LC50	
		static 5.89 - 7.81: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		flow-through 5.8: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		semi-static 11.0 - 15.0: 96 h	
		Lepomis macrochirus mg/L LC50	
		static 50.87 - 70.34: 96 h Poecilia	
		reticulata mg/L LC50 static 14.1 -	
		17.16: 96 h Oncorhynchus mykiss	
		mg/L LC50 static	
Methyl Isobutyl Ketone	400: 96 h Pseudokirchneriella	496 - 514: 96 h Pimephales	170: 48 h Daphnia magna mg/L
108-10-1	subcapitata mg/L EC50	promelas mg/L LC50 flow-through	EC50
Diisodecyl Phthalate	1.3: 96 h Pseudokirchneriella	1: 96 h Pimephales promelas mg/L	0.18: 48 h Daphnia magna mg/L
68515-49-1		LC50 flow-through 1: 96 h	EC50
00313-49-1	subcapitata mg/L EC50		EC30
		Oncorhynchus mykiss mg/L LC50	
		static 0.55: 96 h Lepomis	
		macrochirus mg/L LC50 static 0.62:	
		96 h Oncorhynchus mykiss mg/L	
		LC50 flow-through 0.66: 96 h	
		Pimephales promelas mg/L LC50	
		static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Toluene 108-88-3	2.7
Methyl Isobutyl Ketone 108-10-1	1.19

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container.

14. TRANSPORT INFORMATION

DOT	

UN/ID no	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	I
Reportable Quantity (RQ)	(Methyl Isobutyl Ketone: RQ (kg)= 2270.00, Toluene: RQ (kg)= 0.454)
Special Provisions	149, B52, IB2, T4, TP1, TP8, TP28
Description	UN1263, Paint, 3, II
Emergency Response Guide	128
Number	

TDG UN/ID no Proper shipping name Hazard class Packing Group Special Provisions Description	UN1263 Paint 3 II 59, 83 UN1263, Paint, 3, II
MEX UN/ID no Proper shipping name Hazard class Special Provisions Packing Group Description	UN1263 Paint 3 163 II UN1263, Paint, 3, II
ICAO (air) UN/ID no Proper shipping name Hazard class Packing Group Special Provisions Description	UN1263 Paint 3 II A3, A72 UN1263, Paint, 3, II
IATA UN Number Proper shipping name Transport hazard class(es) Packing Group ERG Code Special Provisions Description	UN1263 Paint 3 II 3L A3, A72 UN1263, Paint, 3, II
IMDG UN Number Transport hazard class(es) Packing Group EmS-No Special Provisions Description	UN1263 3 II F-E, S-E 163 UN1263, Paint, 3, II, (6°C c.c.)
<u>RID</u> UN/ID no Proper shipping name Transport hazard class(es) Packing Group Classification code Special Provisions Description Labels	UN1263 Paint 3 II F1 163, 640C, 650 UN1263, Paint, 3, II 3
ADR UN Number Proper shipping name Transport hazard class(es) Packing Group Classification code Tunnel restriction code Special Provisions Description Labels	UN1263 Paint 3 II F1 (D/E) 163, 640C, 650 UN1263, Paint, 3, II, (D/E) 3

Proper shipping name	Paint
Transport hazard class(es)	3
Packing Group	II
Classification code	F1
Special Provisions	163, 640C, 650
Description	UN1263, Paint, 3, II
Hazard label(s)	3
Limited quantity (LQ)	5 L
Ventilation	VE01
Equipment Requirements	PP, EX, A

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies *

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %	
Toluene - 108-88-3	1.0	
Methyl Isobutyl Ketone - 108-10-1	0.1	

SARA 311/312 Hazard Categories

Acute health hazard Chronic Health Hazard	Yes No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	Х	Х
Diisodecyl Phthalate 68515-49-1	-	X	-	-

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Toluene	1000 lb 1 lb	-	RQ 1000 lb final RQ
108-88-3			RQ 454 kg final RQ RQ 1 lb final
			RQ
			RQ 0.454 kg final RQ
Methyl Isobutyl Ketone	5000 lb	-	RQ 5000 lb final RQ
108-10-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65	
Toluene - 108-88-3	Developmental	
Methyl Isobutyl Ketone - 108-10-1	Carcinogen	
	Developmental	
Titanium dioxide - 13463-67-7	Carcinogen	
Diisodecyl Phthalate - 68515-49-1	Developmental	
Silica, Amorphous fumed - 7631-86-9	Carcinogen	
Ethyl Benzene - 100-41-4	Carcinogen	
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen	
	Developmental	
	Male Reproductive	
Cumene - 98-82-8	Carcinogen	
Naphthalene - 91-20-3	Carcinogen	
Vinyl chloride - 75-01-4	Carcinogen	
Acetaldehyde - 75-07-0	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Toluene	Х	Х
108-88-3		
Methyl Isobutyl Ketone	Х	Х
108-10-1		
Titanium dioxide	Х	Х
13463-67-7		
Phosphoric Acid	Х	Х
7664-38-2		

Chemical name	Pennsylvania
Toluene 108-88-3	X
Methyl Isobutyl Ketone 108-10-1	Х
Titanium dioxide 13463-67-7	X
Diisodecyl Phthalate 68515-49-1	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present individually at 1% by weight, or greater):

Chemical name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Toluene	34.68%	2.92
108-88-3		
Methyl Isobutyl Ketone	32.00%	2.69
108-10-1		

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA

Health hazards 2

Health hazards 2*

Flammability 3

Flammability 3

* = Chronic Health Hazard

Instability 0 Physical hazards 0 Physical and chemical properties - Personal protection X

HMIS Heal Chronic Hazard Star Legend

20-Apr-2022

Revision Date Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet