

SAFETY DATA SHEET

Revision Date 05-Dec-2022 Version 5

1. IDENTIFICATION

Product identifier

Product Name Multi-Thane 330 Mildew Resistant High Solids Acrylic Polyurethane Cotton White (Pt A)

Other means of identification

Product Code IG-1260 UN/ID no UN1263 SKU(s) None

Recommended use of the chemical and restrictions on use

Recommended Use No information available. Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Diamond Vogel 1020 Albany Place SE Orange City, IA 51041 Phone: (712) 737-4993 Fax: (712) 737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

Emergency Overview

Danger

Hazard statements

Harmful if inhaled

May cause an allergic skin reaction

May cause genetic defects

May cause cancer

May cause respiratory irritation. May cause drowsiness or dizziness

Flammable liquid and vapor

Appearance No information available

Physical state Liquid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- · May be harmful if swallowed
- · Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Titanium dioxide	13463-67-7	10 - 30	*
Butyl Acetate	123-86-4	10 - 30	*
Methyl Amyl Ketone	110-43-0	7 - 13	*
Aromatic 100	64742-95-6	1 - 5	*
3-iodo-2-propynyl butyl carbamate	55406-53-6	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin Contact Wash skin with soap and water.

Inhalation Remove to fresh air.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Flammable.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Titanium dioxide	Titanium dioxide TWA: 0.2 mg/m³ nanoscale		IDLH: 5000 mg/m ³
13463-67-7	respirable particulate matter	TWA: 5 mg/m³ respirable fraction	TWA: 2.4 mg/m ³ CIB 63 fine
	TWA: 2.5 mg/m³ finescale		TWA: 0.3 mg/m³ CIB 63 ultrafine,
	respirable particulate matter		including engineered nanoscale
Butyl Acetate	STEL: 150 ppm	TWA: 150 ppm	IDLH: 1700 ppm
123-86-4	TWA: 50 ppm	TWA: 710 mg/m ³	TWA: 150 ppm
		(vacated) TWA: 150 ppm	TWA: 710 mg/m ³
		(vacated) TWA: 710 mg/m ³	STEL: 200 ppm
		(vacated) STEL: 200 ppm	STEL: 950 mg/m ³
		(vacated) STEL: 950 mg/m ³	
Methyl Amyl Ketone	TWA: 50 ppm	TWA: 100 ppm	IDLH: 800 ppm
110-43-0		TWA: 465 mg/m ³	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 465 mg/m ³
		(vacated) TWA: 465 mg/m ³	_

NIOSH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection No special technical protective measures are necessary.

Skin and body protectionNo special technical protective measures are necessary.

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

AppearanceNo information availableOdorNo information availableColorNo information availableOdor thresholdNo information available

Property Values Remarks • Method

pH No information available

Melting point / freezing pointNo information availableBoiling point / boiling range>= 80 °C / 176 °FFlash point33 °C / 92 °FEvaporation rateNo information availableFlammability (solid, gas)No information available

Flammability (solid, gas) Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Specific Gravity 1.33

Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available No information available **Decomposition temperature** Kinematic viscosity No information available Dynamic viscosity No information available **Explosive properties** No information available **Oxidizing properties** No information available

Other Information

Softening pointNo information availableMolecular weightNo information available

Liquid Density 11.05 lbs/gal

Bulk density No information available

Percent solids by weight 73.9% Percent volatile by weight 26.1% Percent solids by volume 59.5% Actual VOC (lbs/gal) 2.9 Actual VOC (grams/liter) 345.7 EPA VOC (lbs/gal) 2.9 EPA VOC (grams/liter) 345.7 EPA VOC (lb/gal solids) 4.8

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

No data available. Inhalation

Eye contact No data available.

No data available. **Skin Contact**

No data available. Ingestion

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat) 4 h
Butyl Acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 0.74 mg/L (Rat) 4 h
Methyl Amyl Ketone 110-43-0	= 1600 mg/kg (Rat)	= 10300 mg/kg (Rabbit)	2000 - 4000 ppm(Rat)6 h
Aromatic 100 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
3-iodo-2-propynyl butyl carbamate 55406-53-6	= 1470 mg/kg (Rat)	> 2000 mg/kg (Rat)	= 0.63 mg/L (Rat) 4 h = 0.67 mg/L (Rat) 4 h = 0.99 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

No information available. **Symptoms**

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available. Germ cell mutagenicity No information available. No information available. Carcinogenicity

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium dioxide	A3	Group 2B	-	Х
13463-67-7				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available. STOT - single exposure No information available. STOT - repeated exposure No information available.

Central nervous system, Eyes, Lungs, Peripheral Nervous System (PNS), Respiratory Target organ effects

system, Skin.

No information available. **Aspiration hazard**

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

18.37% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Butyl Acetate	674.7: 72 h Desmodesmus	17 - 19: 96 h Pimephales promelas	-

123-86-4	subspicatus mg/L EC50	mg/L LC50 flow-through 100: 96 h	
		Lepomis macrochirus mg/L LC50	
		static	
Methyl Amyl Ketone	-	126 - 137: 96 h Pimephales	-
110-43-0		promelas mg/L LC50 flow-through	
Aromatic 100	-	9.22: 96 h Oncorhynchus mykiss	6.14: 48 h Daphnia magna mg/L
64742-95-6		mg/L LC50	EC50
3-iodo-2-propynyl butyl carbamate	-	0.049 - 0.079: 96 h Oncorhynchus	-
55406-53-6		mykiss mg/L LC50 flow-through	
		0.05 - 0.089: 96 h Oncorhynchus	
		mykiss mg/L LC50 0.14 - 0.32: 96 h	
		Lepomis macrochirus mg/L LC50	
		flow-through 0.18 - 0.23: 96 h	
		Pimephales promelas mg/L LC50	
		flow-through	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Butyl Acetate	1.81
123-86-4	2.3
Methyl Amyl Ketone	2.26
110-43-0	
3-iodo-2-propynyl butyl carbamate	2.88
55406-53-6	

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

14. TRANSPORT INFORMATION

DOT

UN/ID no UN1263
Proper shipping name Paint
Hazard class 3
Packing Group III

Reportable Quantity (RQ) (Butyl Acetate: RQ (kg)= 2270.00) **Special Provisions** B1, B52, IB3, T2, TP1, TP29

Description UN1263, Paint, 3, III

Emergency Response Guide 128

Number

TDG

UN/ID no UN1263
Proper shipping name Paint
Hazard class 3
Packing Group III
Special Provisions 59, 83

Description UN1263, Paint, 3, III

MEX

UN/ID no UN1263
Proper shipping name Paint
Hazard class 3
Special Provisions 163, 223
Packing Group III

Description UN1263, Paint, 3, III

ICAO (air)

UN/ID no UN1263
Proper shipping name Paint
Hazard class 3
Packing Group III
Special Provisions A3, A72

Description UN1263, Paint, 3, III

IATA

UN Number UN1263
Proper shipping name Paint
Transport hazard class(es) 3
Packing Group III
ERG Code 3L
Special Provisions A3, A72

Description UN1263, Paint, 3, III

IMDG

 UN Number
 UN1263

 Transport hazard class(es)
 3

 Packing Group
 III

 EmS-No
 F-E, S-E

 Special Provisions
 163, 223, 955

Description UN1263, Paint, 3, III, (33°C c.c.)

RID

UN/ID no
Proper shipping name
Paint
Transport hazard class(es)
Packing Group
Classification code
UN1263
Paint
3
III
F1

Special Provisions163, 640E, 650DescriptionUN1263, Paint, 3, III

Labels 3

<u>ADR</u>

UN Number UN1263
Proper shipping name Paint
Transport hazard class(es) 3
Packing Group III
Classification code F1
Tunnel restriction code (D/E)

Special Provisions 163, 640E, 650

Description UN1263, Paint, 3, III, (D/E)

Labels 3

ADN

Proper shipping name Paint Transport hazard class(es) 3
Packing Group III
Classification code F1

Special Provisions 163, 640E, 650 **Description** UN1263, Paint, 3, III

Hazard label(s) 3

Limited quantity (LQ) 5 L Ventilation VE01 Equipment Requirements PP, EX, A

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies *

Leaend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard No
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl Acetate 123-86-4	5000 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Butyl Acetate	5000 lb	-	RQ 5000 lb final RQ
123-86-4			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Silica, Amorphous fumed - 7631-86-9	Carcinogen
Cumene - 98-82-8	Carcinogen
Ethyl Benzene - 100-41-4	Carcinogen
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen
	Developmental
	Male Reproductive
Formaldehyde - 50-00-0	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Titanium dioxide	X	X

^{*} This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

13463-67-7		
Butyl Acetate	X	X
123-86-4		
Methyl Amyl Ketone	X	X
110-43-0		
2,4 Pentane Dione	X	X
123-54-6		

Chemical name	Pennsylvania
Titanium dioxide 13463-67-7	X
Butyl Acetate 123-86-4	X
Methyl Amyl Ketone 110-43-0	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

This product contains no Hazardous Air Pollutants individually at 1% by weight, or greater.

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0 Physical and chemical

properties -

HMIS Health hazards 2 * Flammability 3 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend *= Chronic Health Hazard

Revision Date 05-Dec-2022

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet