

SAFETY DATA SHEET

Revision Date 07-Dec-2022 Version 5

1. IDENTIFICATION

Product identifier

Product Name Aisle Ease Gloss Safety Marking Yellow

Other means of identification

Product Code MC-3609 SKU(s) None

Recommended use of the chemical and restrictions on use
Recommended Use
Uses advised against
No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Diamond Vogel 1020 Albany Place SE Orange City, IA 51041 Phone: (712) 737-4993 Fax: (712) 737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity Category 1A

Emergency Overview

Danger

Hazard statements

May cause cancer



Appearance No information available

Physical state Liquid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

• Causes mild skin irritation

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Ethylene Glycol Butyl Ether	111-76-2	1 - 5	*
Kaolin	1332-58-7	1 - 5	*
Ethanol	64-17-5	1 - 5	*
Titanium dioxide	13463-67-7	1 - 5	*
Talc (powder)	14807-96-6	0.1 - 1	*
Ammonium Hydroxide	1336-21-6	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin Contact Wash skin with soap and water.

Inhalation Remove to fresh air.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use personal protective equipment as required. Dam up. Cover liquid spill with sand, earth

or other non-combustible absorbent material. Take up mechanically, placing in appropriate

containers for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materialsNone known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Ethylene Glycol Butyl Ether	TWA: 20 ppm	TWA: 50 ppm	IDLH: 700 ppm
111-76-2		TWA: 240 mg/m ³	TWA: 5 ppm
		(vacated) TWA: 25 ppm	TWA: 24 mg/m ³
		(vacated) TWA: 120 mg/m ³	
		(vacated) S*	
		S*	
Kaolin	TWA: 2 mg/m³ particulate matter	TWA: 15 mg/m³ total dust	TWA: 10 mg/m ³ total dust
1332-58-7	containing no asbestos and <1%	TWA: 5 mg/m ³ respirable fraction	TWA: 5 mg/m³ respirable dust
	crystalline silica, respirable	(vacated) TWA: 10 mg/m3 total dust	
	particulate matter	(vacated) TWA: 5 mg/m³ respirable	
		fraction	
Ethanol	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m ³
		(vacated) TWA: 1900 mg/m ³	
Titanium dioxide	TWA: 0.2 mg/m³ nanoscale	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m ³
13463-67-7	respirable particulate matter	TWA: 5 mg/m³ respirable fraction	TWA: 2.4 mg/m ³ CIB 63 fine
	TWA: 2.5 mg/m³ finescale		TWA: 0.3 mg/m ³ CIB 63 ultrafine,
	respirable particulate matter		including engineered nanoscale
Talc (powder)	TWA: 2 mg/m³ particulate matter	(vacated) TWA: 2 mg/m³ respirable	IDLH: 1000 mg/m ³
14807-96-6	containing no asbestos and <1%	dust <1% Crystalline silica,	TWA: 2 mg/m³ containing no
	crystalline silica, respirable	containing no Asbestos	Asbestos and <1% Quartz

particulate matter TWA: 20 mppcf if 1% Quartz or respirable dust more;use Quartz limit

NIOSH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection No special technical protective measures are necessary.

Skin and body protectionNo special technical protective measures are necessary.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

AppearanceNo information availableOdorNo information availableColorNo information availableOdor thresholdNo information available

 Property
 Values
 Remarks • Method

 pH
 No information available

pH No information available No information available No information available No information available Soiling point / boiling range $>= 64 \, ^{\circ}\text{C} \, / \, 148 \, ^{\circ}\text{F}$ Flash point $>= 94 \, ^{\circ}\text{C} \, / \, > 201 \, ^{\circ}\text{F}$ No information available Flammability (solid, gas) No information available Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Specific Gravity 1.08

Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dvnamic viscosity** No information available **Explosive properties** No information available Oxidizing properties No information available

Other Information

Softening point No information available Molecular weight No information available

Liquid Density 9.03 lbs/gal

Bulk density No information available

Percent solids by weight
Percent volatile by weight
Percent solids by volume
Actual VOC (lbs/gal)
Actual VOC (grams/liter)
EPA VOC (grams/liter)
EPA VOC (grams/liter)
EPA VOC (lbs/gal solids)
43.6%
6.1%
66.1
EPA VOC (lbs/gal)
1.2

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation No data available.

Eye contact No data available.

Skin Contact No data available.

Ingestion No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene Glycol Butyl Ether 111-76-2	= 470 mg/kg (Rat)	= 435 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
Ethanol 64-17-5	= 7060 mg/kg (Rat)	-	= 116.9 mg/L (Rat) 4 h = 133.8 mg/L (Rat) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat) 4 h
Talc (powder) 14807-96-6	= 55,000 mg/kg (Rat)	-	-
Ammonium Hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicityNo information available.
No information available.

Carcinogenicity Ethanol has been shown to be carcinogenic in long-term studies only when consumed as

alcoholic beverage.

Chemical name	ACGIH	IARC	NTP	OSHA
Ethylene Glycol Butyl Ether 111-76-2	А3	Group 3	-	-
Ethanol 64-17-5	A3	Group 1	Known	Х
Titanium dioxide 13463-67-7	A3	Group 2B	-	Х
Talc (powder) 14807-96-6	-	Group 3	-	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Chronic toxicity Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic

beverage. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Contains a known or suspected

reproductive toxin.

Target organ effects blood, Central nervous system, Eyes, Hematopoietic System, kidney, liver, Lungs,

Reproductive System, Respiratory system, Skin.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

5.44% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Ethylene Glycol Butyl Ether	-	1490: 96 h Lepomis macrochirus	1000: 48 h Daphnia magna mg/L
111-76-2		mg/L LC50 static 2950: 96 h	EC50
		Lepomis macrochirus mg/L LC50	
Ethanol	-	12.0 - 16.0: 96 h Oncorhynchus	9268 - 14221: 48 h Daphnia magna
64-17-5		mykiss mL/L LC50 static 13400 -	mg/L LC50 2: 48 h Daphnia magna
		15100: 96 h Pimephales promelas	mg/L EC50 Static
		mg/L LC50 flow-through 100: 96 h	_
		Pimephales promelas mg/L LC50	
		static	
Talc (powder)	-	100: 96 h Brachydanio rerio g/L	-
14807-96-6		LC50 semi-static	
Ammonium Hydroxide	-	8.2: 96 h Pimephales promelas	0.66: 48 h Daphnia pulex mg/L
1336-21-6		mg/L LC50	EC50 0.66: 48 h water flea mg/L
			FC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Ethylene Glycol Butyl Ether 111-76-2	0.81
Ethanol	-0.35
64-17-5	

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

14. TRANSPORT INFORMATION

DOT Not regulated Not regulated TDG Not regulated **MEX** ICAO (air) Not regulated Not regulated **IATA** Not regulated **IMDG** RID Not regulated Not regulated ADR ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies *

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Ethylene Glycol Butyl Ether - 111-76-2	1.0

SARA 311/312 Hazard Categories

^{*} This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ammonium Hydroxide 1336-21-6	1000 lb	-	-	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ammonium Hydroxide	1000 lb	-	RQ 1000 lb final RQ
1336-21-6			RQ 454 kg final RQ

US State Regulations

<u>California Proposition 65</u>
This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Ethanol - 64-17-5	Carcinogen
	Developmental
Titanium dioxide - 13463-67-7	Carcinogen
Methanol - 67-56-1	Developmental
Silica, Amorphous fumed - 7631-86-9	Carcinogen
Methyl Isobutyl Ketone - 108-10-1	Carcinogen
, , ,	Developmental
Formaldehyde - 50-00-0	Carcinogen
Zinc Chromate - 13530-65-9	Carcinogen
	Developmental
	Female Reproductive
	Male Reproductive
Lead - 7439-92-1	Carcinogen
	Developmental
	Female Reproductive
	Male Reproductive
Mercury - 7439-97-6	Developmental
Nickel - 7440-02-0	Carcinogen
Cadmium - 7440-43-9	Carcinogen
	Developmental
	Male Reproductive
Cobalt - 7440-48-4	Carcinogen
Acetaldehyde - 75-07-0	Carcinogen
Ethylene oxide - 75-21-8	Carcinogen
·	Developmental
	Female Reproductive
	Male Reproductive
1,4-Dioxane - 123-91-1	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Ethylene Glycol Butyl Ether 111-76-2	X	X
Kaolin 1332-58-7	X	Х
Ethanol 64-17-5	X	X
Titanium dioxide 13463-67-7	X	X

Talc (powder) 14807-96-6	X	Х
Ammonium Hydroxide 1336-21-6	X	X

Chemical name	Pennsylvania
Ethylene Glycol Butyl Ether	X
111-76-2	
Kaolin	X
1332-58-7	
Ethanol	X
64-17-5	
Titanium dioxide	X
13463-67-7	

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

This product contains no Hazardous Air Pollutants individually at 1% by weight, or greater.

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 1 Instability 0 Physical and chemical

properties -

HMIS Health hazards 2 * Flammability 1 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend *= Chronic Health Hazard

Revision Date 07-Dec-2022

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet