

## **TECHNICAL DATA SHEET**

**Peridium** TGIC Polyester

PRODUCT CODE: PLX2903-04

**DESCRIPTION:** Window Grey (RAL 7040)

**POWDER PROPERTIES:** 

Specific Gravity:  $1.29 \pm 0.05$ 

Theoretical Coverage @ 1 mil (square feet per pound):  $149 \pm 4$ 

**CURED POWDER PROPERTIES (1.8 to 2.2 mils DFT)** 

Cure Schedule (Time at Substrate Temperature): 10' @ 390 °F PMT

Substrate for Testing: B1000 0.032 CRS

Gloss: 75-85 @ 60°

PCI Powder Smoothness: 6

Pencil Hardness: ASTM D3363 2H+

Direct/Reverse Impact (inch-pounds): ASTM D2794 160 / 160

Adhesion, Crosshatch: ASTM D3359 5B

Flexibility, Mandrel Bend: ASTM D522 1/8 in dia, no fracture

Salt Spray – 1000 hrs: ASTM B117 Pass

Humidity – 1000 hrs: ASTM D2247 Pass

## Additional Technical Data available upon request

## **STORAGE STABILITY**

Maintain storage temperatures below 80°F. Protect virgin and reclaimed powder from excessive heat and humidity. Shelf life ranges from 6 months to over 1 year depending on storage conditions.

## LIMITED WARRANTY

Since Diamond Vogel does not control the application of its product, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Diamond Vogel's liability will under no circumstances exceed replacement of the product.



Rev: 12/2018