

Revision Date 17-Feb-2020

Version 6

1. IDENTIFICATION

Product identifier

Product Name White ALK ACR ZN FD

Other means of identification

Product Code TM-1733

UN/ID no UN1263

SKU(s) None

Recommended use of the chemical and restrictions on use

Recommended Use No information available.

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Diamond Vogel
1020 Albany Place SE
Orange City, IA 51041
Phone: (712) 737-4993
Fax: (712) 737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Emergency Overview

Danger

Hazard statements

Causes serious eye irritation
May cause an allergic skin reaction
May cause genetic defects
May cause cancer
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor

**Appearance** No information available**Physical state** Liquid**Odor** No information available**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other Information**

- Causes mild skin irritation
- Very toxic to aquatic life with long lasting effects
- Toxic to aquatic life

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Talc (powder)	14807-96-6	10 - 30	*
Calcium carbonate	1317-65-3	10 - 30	*
Methyl Ethyl Ketone	78-93-3	7 - 13	*
Titanium dioxide	13463-67-7	5 - 10	*
Aliphatic Hydrocarbon	64742-49-0	3 - 7	*
Solvent Naphtha, Light Aliphatic	64742-89-8	1 - 5	*

Heptane	142-82-5	1 - 5	*
Chlorinated paraffin waxes	63449-39-8	1 - 5	*
Crystalline Silica	14808-60-7	0.1 - 1	*
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin Contact	Wash skin with soap and water.
Inhalation	Remove to fresh air.
Ingestion	Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Extremely flammable.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Remove all sources of ignition.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Talc (powder) 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Calcium carbonate 1317-65-3	TWA: 10 mg/m ³ inhalable particles TWA: 3 mg/m ³ respirable particles	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Methyl Ethyl Ketone 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m ³ (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m ³	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³
Crystalline Silica 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/((%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/((%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

NIOSH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	No special technical protective measures are necessary.
Skin and body protection	No special technical protective measures are necessary.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	No information available
Appearance	No information available	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	>= 64 °C / 148 °F	
Flash point	-7 °C / 20 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	1.39	
Water solubility	No information available	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
Liquid Density	11.62 lbs/gal
Bulk density	No information available
Percent solids by weight	72.0%
Percent volatile by weight	28.0%
Percent solids by volume	48.5%
Actual VOC (lbs/gal)	3.3
Actual VOC (grams/liter)	390.3
EPA VOC (lbs/gal)	3.3
EPA VOC (grams/liter)	390.3
EPA VOC (lb/gal solids)	6.7

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin Contact	No data available.
Ingestion	No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Talc (powder) 14807-96-6	= 55,000 mg/kg (Rat)	-	-
Calcium carbonate 1317-65-3	= 6450 mg/kg (Rat)	-	-
Methyl Ethyl Ketone 78-93-3	= 2483 mg/kg (Rat) = 2737 mg/kg (Rat)	= 5000 mg/kg (Rabbit) = 6480 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Aliphatic Hydrocarbon 64742-49-0	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h
Solvent Naphtha, Light Aliphatic 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
Heptane 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h
Chlorinated paraffin waxes 63449-39-8	= 26100 mg/kg (Rat) > 21500 µL/kg (Rat)	> 10 mL/kg (Rabbit)	-
Crystalline Silica 14808-60-7	> 22,500 mg/kg (Rat)	-	-
Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Chemical name	ACGIH	IARC	NTP	OSHA

Talc (powder) 14807-96-6	-	Group 3	-	X
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Chlorinated paraffin waxes 63449-39-8	-	Group 2B	-	X
Crystalline Silica 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

No information available.

Target organ effects

Central nervous system, Central Vascular System (CVS), Eyes, Lungs, Respiratory system, Skin.

Aspiration hazard

No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects

35.61% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Talc (powder) 14807-96-6	-	100: 96 h Brachydanio rerio g/L LC50 semi-static	-
Methyl Ethyl Ketone 78-93-3	-	3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through	5091: 48 h Daphnia magna mg/L EC50 520: 48 h Daphnia magna mg/L EC50 4025 - 6440: 48 h Daphnia magna mg/L EC50 Static
Aliphatic Hydrocarbon 64742-49-0	-	8.41: 96 h Oncorhynchus mykiss mg/L LC50 semi-static, closed	2.6: 96 h Chaetogammarus marinus mg/L LC50
Solvent Naphtha, Light Aliphatic 64742-89-8	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50	-	-
Heptane 142-82-5	-	375.0: 96 h Cichlid fish mg/L LC50	10: 24 h Daphnia magna mg/L EC50
Chlorinated paraffin waxes 63449-39-8	-	300: 96 h Lepomis macrochirus mg/L LC50 static 0.0109: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 94.5 - 271: 96 h Oncorhynchus mykiss mg/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 0.1: 96 h Lepomis macrochirus mg/L LC50 flow-through	102: 24 h Daphnia magna mg/L EC50
Methyl Ethyl Ketoxime 96-29-7	83: 72 h Desmodesmus subspicatus mg/L EC50	760: 96 h Poecilia reticulata mg/L LC50 static 320 - 1000: 96 h Leuciscus idus mg/L LC50 static 777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through	750: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Methyl Ethyl Ketone 78-93-3	0.3
Heptane 142-82-5	4.66
Chlorinated paraffin waxes 63449-39-8	>6
Methyl Ethyl Ketoxime 96-29-7	0.65

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001 U220 U239 U154 U159 U165 U055

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl Ethyl Ketone 78-93-3	U159	Included in waste streams: F005, F039	200.0 mg/L regulatory level	U159

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Methyl Ethyl Ketone 78-93-3	Toxic mixture of acetone, methyl acetate, and methyl alcohol Ignitable mixture of acetone, methyl acetate, and methyl alcohol
Heptane 142-82-5	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Reportable Quantity (RQ) (Xylene: RQ (kg)= 45.40, Methyl Ethyl Ketone: RQ (kg)= 2270.00)
Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28
Description UN1263, Paint, 3, II
Emergency Response Guide Number 128

TDG

UN/ID no UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Special Provisions 59, 83
Description UN1263, Paint, 3, II

MEX

UNID no UN1263
Proper shipping name Paint
Hazard class 3
Special Provisions 163
Packing Group II
Description UN1263, Paint, 3, II

ICAO (air)

UNID no UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Special Provisions A3, A72
Description UN1263, Paint, 3, II

IATA

UN Number UN1263
Proper shipping name Paint
Transport hazard class(es) 3
Packing Group II
ERG Code 3L
Special Provisions A3, A72
Description UN1263, Paint, 3, II

IMDG

UN Number UN1263
Transport hazard class(es) 3
Packing Group II
EmS-No F-E, S-E
Special Provisions 163
Description UN1263, Paint, 3, II, (-7°C c.c.)

RID

UNID no UN1263
Proper shipping name Paint
Transport hazard class(es) 3
Packing Group II
Classification code F1
Special Provisions 163, 640C, 650
Description UN1263, Paint, 3, II
Labels 3

ADR

UN Number UN1263
Proper shipping name Paint
Transport hazard class(es) 3
Packing Group II
Classification code F1
Tunnel restriction code (D/E)
Special Provisions 163, 640C, 650
Description UN1263, Paint, 3, II, (D/E)
Labels 3

ADN

Proper shipping name Paint
Transport hazard class(es) 3
Packing Group II
Classification code F1
Special Provisions 163, 640C, 650
Description UN1263, Paint, 3, II
Hazard label(s) 3
Limited quantity (LQ) 5 L
Ventilation VE01

Equipment Requirements PP, EX, A

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies *

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard No
 Chronic Health Hazard No
 Fire hazard Yes
 Sudden release of pressure hazard No
 Reactive Hazard No

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methyl Ethyl Ketone 78-93-3	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen
Methanol - 67-56-1	Developmental
Ethyl Benzene - 100-41-4	Carcinogen
Naphthalene - 91-20-3	Carcinogen
Cumene - 98-82-8	Carcinogen
Toluene - 108-88-3	Developmental

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Talc (powder) 14807-96-6	X	X
Calcium carbonate 1317-65-3	X	X
Methyl Ethyl Ketone 78-93-3	X	X
Titanium dioxide 13463-67-7	X	X
Heptane 142-82-5	X	X
Xylene 1330-20-7	X	X
Crystalline Silica 14808-60-7	X	X

Methanol 67-56-1	X	X
---------------------	---	---

Chemical name	Pennsylvania
Talc (powder) 14807-96-6	X
Calcium carbonate 1317-65-3	X
Methyl Ethyl Ketone 78-93-3	X
Titanium dioxide 13463-67-7	X
Heptane 142-82-5	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

This product contains no Hazardous Air Pollutants individually at 1% by weight, or greater.

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	Physical and chemical properties -
HMIS	Health hazards 2 *	Flammability 3	Physical hazards 0	Personal protection X
<i>Chronic Hazard Star Legend</i>	<i>* = Chronic Health Hazard</i>			

Revision Date 17-Feb-2020

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet