Diamond Vogel INDUSTRIAL WOOD COATINGS

Triclad Omni Water Base Wiping Stain

Prod	uct	Codes	

Clear	23-500
Black	23-505
Burnt Sienna	23-510
Burnt Umber	23-515
Dark Umber	23-520
Red	23-525
Raw Sienna	23-530
Raw Umber	23-535
Van Dyke Brown	23-540
White	23-545
Trans Red	23-550
Violet	23-555
Trans Yellow	23-560
Deep Red	23-565
Strong White	23-570

Description

Water base stain matching system based fourteen stand alone stains that can be intermixed to make an infinite amount of colors.

Features

- Brush, spray, wipe, or dip application
- Fast Dry Times
- Excellent Clarity
- Rich and Deep Colors

PRODUCT DATA SHEET

Surface Preparation

New Work:

White wood sand to 220 grit or 320 grit. Successively sand from coarse grits up to fine grits. Proper sanding is critical for consistent color.

Mixing Instructions

Mixing:

Agitate stains well to remove solids from the bottom of the container before intermixing bases. All bases are equally balance to avoid over pigmentation and can be use as stand alone stains. Use clear base to lighten achieved color.

Application

Brush, spray, wipe, or dip application

Dry Times at 68° F			
Touchable	10 minutes		
Ready for Recoat	30 minutes		
Drying Conditions:			
Dry times are averages. Variables such			
as wood type, wiping, temperature,			

humidity and air movement will affect dry time. Always allow stain to thoroughly dry before top-coating to avoid finishing problems.

Forced Drying:

5 minutes at 125° F

Recommended Topcoat

Triclad Omni maybe top coated with most clear top coats, including water base, lacquer, conversion varnish and most two-component systems.

Cautions

Safety Data Sheets are available from your Diamond Vogel representative. Prior to use of this product, obtain and review the Safety Data Sheet for health and safety information. Read and observe all precautionary notices on container labels.

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Diamond Vogel does not control the applicaiton of its products, or the condition of the surfaces to which they are applied, Diamond Vogel liability will under no circumstances exceed replacement of the product. All technical information is subject to change without notice.