

# SAFETY DATA SHEET

Revision Date 21-Mar-2017 Version 2

# 1. IDENTIFICATION

**Product identifier** 

Product Name Yellow MN HB TRF FD

Other means of identification

Product Code UC35-45463 SKU(s) None

Recommended use of the chemical and restrictions on use
Recommended Use
Uses advised against
No information available

Details of the supplier of the safety data sheet

**Manufacturer Address** 

Diamond Vogel Paint 1020 Albany Place SE Orange City, IA 51041 Phone: 712-737-4993

Fax: 712-737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

# 2. HAZARDS IDENTIFICATION

### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 1

**Emergency Overview** 

### Danger

### Hazard statements

May cause cancer Causes damage to organs



Appearance No information available

Physical state liquid

Odor No information available

### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

#### **Precautionary Statements - Response**

IF exposed: Call a POISON CENTER or doctor/physician

# **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

### Other Information

- · May be harmful if swallowed
- · Harmful to aquatic life with long lasting effects
- Harmful to aquatic life

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Calcium carbonate	1317-65-3	30 - 60	*
Methanol	67-56-1	1 - 5	*
Texanol	25265-77-4	1 - 5	*
Titanium dioxide	13463-67-7	1 - 5	*
Crystalline Silica	14808-60-7	0.1 - 1	*
Heavy Paraffinic Distillate	64742-54-7	0.1 - 1	*
Talc (powder)	14807-96-6	0.1 - 1	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### Description of first aid measures

**Eye contact** Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

**Skin Contact** Wash skin with soap and water.

**Inhalation** Remove to fresh air.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

Indication of any immediate medical attention and special treatment needed

# 5. FIRE-FIGHTING MEASURES

\_\_\_\_\_

#### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

No information available.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

# Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use personal protective equipment as required. Dam up. Cover liquid spill with sand, earth

or other non-combustible absorbent material. Take up mechanically, placing in appropriate

containers for disposal. Clean contaminated surface thoroughly.

# 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

**Incompatible materials**None known based on information supplied.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

Exposure Guidelines

	Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium carbonate -		TWA: 15 mg/m³ total dust	TWA: 10 mg/m³ total dust	
	1317-65-3		TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m³ respirable dust
			(vacated) TWA: 15 mg/m <sup>3</sup> total dust	
			(vacated) TWA: 5 mg/m³ respirable	
			fraction	

Methanol	STEL: 250 ppm	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup>	IDLH: 6000 ppm
67-56-1	67-56-1 TWA: 200 ppm S*		TWA: 200 ppm
			TWA: 260 mg/m <sup>3</sup>
		(vacated) TWA: 260 mg/m <sup>3</sup>	STEL: 250 ppm
		(vacated) STEL: 250 ppm	STEL: 325 mg/m <sup>3</sup>
		(vacated) STEL: 325 mg/m <sup>3</sup>	_
		(vacated) S*	
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7	TVV ta 10 mg/m	(vacated) TWA: 10 mg/m³ total dust	
	TMA: 0.025 mg/m³ roopiroble	TWA: 50 μg/m³ TWA: 50 μg/m³	IDLH: 50 mg/m³ respirable dust
Crystalline Silica	TWA: 0.025 mg/m³ respirable	excludes construction work.	
14606-60-7	14808-60-7 particulate matter		TWA: 0.05 mg/m³ respirable dust
		exposures that result from the	
		processing of sorptive clays	
		(vacated) TWA: 0.1 mg/m <sup>3</sup>	
		respirable dust	
		: (250)/(%SiO2 + 5) mppcf TWA	
		respirable fraction	
		: (10)/(%SiO2 + 2) mg/m³ TWA	
		respirable fraction	
Talc (powder)  14807-96-6  TWA: 2 mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter		(vacated) TWA: 2 mg/m3 respirable	IDLH: 1000 mg/m <sup>3</sup>
		dust <1% Crystalline silica,	TWA: 2 mg/m³ containing no
		containing no Asbestos	Asbestos and <1% Quartz
		TWA: 20 mppcf if 1% Quartz or	respirable dust
		more, use Quartz limit	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face protection** No special technical protective measures are necessary.

**Skin and body protection**No special technical protective measures are necessary.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Remarks • Method

provided in accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state liquid

AppearanceNo information availableOdorNo information availableColorNo information availableOdor thresholdNo information available

<u>Property</u> <u>Values</u>

PH No information available

Melting point/freezing point

Boiling point / boiling range

Flash point

Evaporation rate

Flammability (solid, gas)

No information available

No information available

No information available

No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Specific Gravity 1.61

Water solubility No information available Solubility in other solvents No information available **Partition coefficient** No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available **Explosive properties** No information available **Oxidizing properties** No information available

#### **Other Information**

Softening pointNo information availableMolecular weightNo information availableVOC Content (%)No information available

**Density** 13.39 lbs/gal

Bulk density No information available

Percent solids by weight 76.4% Percent volatile by weight 4.3% Percent solids by volume 61.0% Actual VOC (lbs/gal) 0.6 Actual VOC (grams/liter) 68.5 EPA VOC (lbs/gal) 8.0 **EPA VOC (grams/liter)** 99.4 EPA VOC (lb/gal solids) 0.9

# 10. STABILITY AND REACTIVITY

# Reactivity

No data available

# **Chemical stability**

Stable under recommended storage conditions.

### **Possibility of Hazardous Reactions**

None under normal processing.

#### Conditions to avoid

Extremes of temperature and direct sunlight.

#### Incompatible materials

None known based on information supplied.

#### **Hazardous Decomposition Products**

None known based on information supplied.

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

Product InformationNo data availableInhalationNo data available.Eye contactNo data available.

**Skin Contact** No data available.

**Ingestion** No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Calcium carbonate 1317-65-3	= 6450 mg/kg (Rat)	-	-
Methanol 67-56-1	= 6200 mg/kg ( Rat )	= 15800 mg/kg ( Rabbit )	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h
Texanol 25265-77-4	= 3200 mg/kg (Rat)	> 15200 mg/kg (Rat)	> 3.55 mg/L (Rat) 6 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Crystalline Silica 14808-60-7	= 500 mg/kg ( Rat )	-	-
Heavy Paraffinic Distillate 64742-54-7	> 15 g/kg (Rat)	-	-
Talc (powder) 14807-96-6	= 55,000 mg/kg (Rat)	-	-

### Information on toxicological effects

Symptoms No information available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	Х
Crystalline Silica 14808-60-7	A2	Group 1	Known	X
Heavy Paraffinic Distillate 64742-54-7	A2	Group 1	Known	X
Talc (powder) 14807-96-6	-	Group 3	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Target Organ Effects Central nervous system, Eyes, Gastrointestinal tract (GI), lungs, Respiratory system, Skin.

Aspiration hazard No information available.

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

# 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

Harmful to aquatic life with long lasting effects

95.16% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Methanol	-	19500 - 20700: 96 h Oncorhynchus	-
67-56-1		mykiss mg/L LC50 flow-through	
		100: 96 h Pimephales promelas	
		mg/L LC50 static 13500 - 17600: 96	
		h Lepomis macrochirus mg/L LC50	
		flow-through 28200: 96 h	
		Pimephales promelas mg/L LC50	
		flow-through 18 - 20: 96 h	
		Oncorhynchus mykiss mL/L LC50	
		static	
Texanol 18.4: 72 h Pseudokirchn		30: 96 h Pimephales promelas mg/L	95: 96 h Daphnia magna mg/L LC50
25265-77-4	subcapitata mg/L EC50	LC50	
Heavy Paraffinic Distillate	-	5000: 96 h Oncorhynchus mykiss	1000: 48 h Daphnia magna mg/L
64742-54-7		mg/L LC50	EC50
Talc (powder)	-	100: 96 h Brachydanio rerio g/L	-
14807-96-6		LC50 semi-static	

# Persistence and degradability

No information available.

### **Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Methanol 67-56-1	-0.77
Texanol 25265-77-4	3.47

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment methods

**Disposal of wastes**Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

US EPA Waste Number U154

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methanol	-	Included in waste stream:	-	U154
67-56-1		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Methanol	Toxic
67-56-1	Ignitable

# 14. TRANSPORT INFORMATION

**DOT** Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies **DSL/NDSL** Complies \* **EINECS/ELINCS** Does not comply \* Does not comply \* **ENCS** Complies \* **IECSC KECL** Complies \* **PICCS** Complies \* Complies \* **AICS** 

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Methanol	1.0

### SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methanol	5000 lb	-	RQ 5000 lb final RQ
67-56-1			RQ 2270 kg final RQ

# **US State Regulations**

# **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
Methanol - 67-56-1	Developmental	
Titanium dioxide - 13463-67-7	Carcinogen	
Crystalline Silica - 14808-60-7	Carcinogen	
Ethylene Glycol - 107-21-1	Developmental	

### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts

<sup>\*</sup> This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Calcium carbonate 1317-65-3	X	X
Methanol 67-56-1	X	X
Titanium dioxide 13463-67-7	X	X
Crystalline Silica 14808-60-7	X	X
Talc (powder) 14807-96-6	X	X

Chemical Name	Pennsylvania
Calcium carbonate 1317-65-3	X
Methanol 67-56-1	X
Titanium dioxide 13463-67-7	X

### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

# Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present individually at 1% by weight, or greater):

Chemical Name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Methanol	2.19%	0.29
67-56-1		

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 1 Instability 0 Physical and Chemical

Properties -

HMIS Health hazards 2 \* Flammability 1 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend \*= Chronic Health Hazard

Revision Date 21-Mar-2017

**Revision Note** 

No information available

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

**End of Safety Data Sheet**