



PRODUCT

State of Minnesota High Build Specification Waterborne Traffic Marking Paint

DESCRIPTION

A high solids, fast drying striping paint suitable for application by airless or air atomized equipment. It meets or exceeds the Minnesota specification for high build traffic marking paint and is recommended for marking and striping streets and highways, as well as driveways, parking lots, sidewalks, curbs, or airport runways. It may be applied to either concrete or asphalt surfaces.

COLORS

White UC15-45472
Yellow UC35-45463

SURFACE PREPARATION

The surface to be coated must be free of any contaminant that will prevent the paint from adhering to the surface. Oil, grease, loose paint chips, gravel, salt films and curing membranes may all interfere with the adhesion of the coating. The surface should be swept clean of all loose contaminants. Visible stains of oils or dirt should be washed from the surface prior to coating. Slick or glossy surfaces, such as hard steel troweled concrete should be abraded to provide surface profile for the coating to adhere.

APPLICATION

Stir material prior to application. Equipment must be clean prior to start. Flush airless lines with water or N-7025. Apply with conventional or airless spray equipment. Small areas may be brushed or rolled. Apply 1 coat at a wet film thickness of 15 mils for standard application or 25 mils for high build application. Allow to dry 5 minutes for standard application or 10 minutes for high build application before allowing traffic to drive over this coating. This coating has been successfully applied through a heated system up to temperatures of 140° F. Heating the coating will decrease the dry time, if surface temperatures, relative humidity, and air movement remain within the requirements for proper application. DO NOT THIN.

ENVIRONMENTAL VARIABLES

Apply when air and surface temperatures are above 50° F. Lower surface and air temperatures will slow the speed of dry. Surface temperatures below 70° F and/or relative humidity greater than 80% may require longer curing times prior to bearing traffic.

CLEAN-UP

Clean up spills immediately with soap and warm water or N-7025 thinner. Clean tools immediately after use with soap and warm water or N-7025 thinner. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment.

CAUTIONS

Do not freeze. Do not apply below 50° F. Do not take internally. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PHYSICAL PROPERTIES

Table with 2 columns: Property Name and Value. Rows include Resin Type (Acrylic), Clean-Up Solvent (Water), Finish (Flat), Solids by Weight (78%), Solids by Volume (62%), VOCs (<150 g/L), Standard Application, Wet Film to Achieve DFT (15 mils), Practical Coverage at Recommended DFT (107 sq.ft./gallon), 4" Lines at 15 mils WFT (320 ft./gallon), Dry Time at 70° F (21°C) and 50% Relative Humidity - Tack Free (<5 minutes), High Build Application, Wet Film to Achieve DFT (25 mils), Practical Coverage at Recommended DFT (62 sq.ft./gallon), 4" Lines at 25 mils WFT (192 ft./gallon), Dry Time at 70° F (21°C) and 50% Relative Humidity - Tack free (<10 minutes).

Revised: August 27, 2018

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Diamond Vogel does not control the application of its products, or the condition of the surfaces to which they are applied, Diamond Vogel's liability will under no circumstances exceed replacement of the product.