

# SAFETY DATA SHEET

Revision Date 20-May-2015 Version 1

# 1. IDENTIFICATION

**Product identifier** 

Product Name Multi-Thane 340 S/G C/B (Pt A)

Other means of identification

 Product Code
 IG-0254

 UN/ID no.
 UN1263

 SKU(s)
 None

Recommended use of the chemical and restrictions on use
Recommended Use
No information available.

Uses advised against

No information available

Details of the supplier of the safety data sheet

**Manufacturer Address** 

Diamond Vogel Paint 1020 Albany Place SE Orange City, IA 51041 Phone: 712-737-4993

Fax: 712-737-499

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

# 2. HAZARDS IDENTIFICATION

# Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Flammable liquids	Category 3

**Emergency Overview** 

# Danger

### Hazard statements

May cause genetic defects May cause cancer Flammable liquid and vapor





Appearance No information available

Physical state liquid

Odor No information available

# **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Use explosion-proof electrical/ ventilating/ lighting/ equipment

# **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

In case of fire: Use CO2, dry chemical, or foam for extinction

### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

#### Other Information

Unknown acute toxicity 0.37% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Butyl Acetate	123-86-4	10 - 30	*
Silica, Amorphous fumed	7631-86-9	5 - 10	*
Methyl Amyl Ketone	110-43-0	3 - 7	*
Crystalline Silica	14808-60-7	3 - 7	*
Aromatic 100	64742-95-6	1 - 5	*
Mineral Spirits	64742-48-9	0.1 - 1	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

# **Description of first aid measures**

**Eye contact**Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

**Skin Contact** Wash skin with soap and water.

**Inhalation** Remove to fresh air.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

Indication of any immediate medical attention and special treatment needed

# 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

Flammable.

**Explosion data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

# Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Use personal protective equipment as required.

**Environmental precautions** 

**Environmental precautions**Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up**Soak up with inert absorbent material.

# 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

**Incompatible materials**None known based on information supplied.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Butyl Acetate	STEL: 200 ppm	TWA: 150 ppm	IDLH: 1700 ppm
123-86-4	TWA: 150 ppm	TWA: 710 mg/m <sup>3</sup>	TWA: 150 ppm
		(vacated) TWA: 150 ppm	TWA: 710 mg/m <sup>3</sup>
		(vacated) TWA: 710 mg/m <sup>3</sup>	STEL: 200 ppm
		(vacated) STEL: 200 ppm	STEL: 950 mg/m <sup>3</sup>
		(vacated) STEL: 950 mg/m <sup>3</sup>	· ·

Silica, Amorphous fumed 7631-86-9	-	(vacated) TWA: 6 mg/m³ <1% Crystalline silica TWA: 20 mppcf	IDLH: 3000 mg/m³ TWA: 6 mg/m³
		: (80)/(% SiO2) mg/m³ TWA	
Methyl Amyl Ketone	TWA: 50 ppm	TWA: 100 ppm	IDLH: 800 ppm
110-43-0	1	TWA: 465 mg/m <sup>3</sup>	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 465 mg/m <sup>3</sup>
		(vacated) TWA: 465 mg/m <sup>3</sup>	_
Crystalline Silica	TWA: 0.025 mg/m <sup>3</sup> respirable	(vacated) TWA: 0.1 mg/m <sup>3</sup>	IDLH: 50 mg/m3 respirable dust
14808-60-7	fraction	respirable dust	TWA: 0.05 mg/m <sup>3</sup> respirable dust
		: (30)/(%SiO2 + 2) mg/m³ TWA	,
		total dust	
		: (250)/(%SiO2 + 5) mppcf TWA	
		respirable fraction	
		: (10)/(%SiO2 + 2) mg/m³ TWA	
		respirable fraction	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face protection** No special technical protective measures are necessary.

**Skin and body protection** No special technical protective measures are necessary.

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Remarks • Method

provided in accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

Physical state liquid

AppearanceNo information availableOdorNo information availableColorNo information availableOdor thresholdNo information available

<u>Property</u> <u>Values</u>

pH No information available
Melting point/freezing point
Boiling point / boiling range
Flash point

No information available
No information available
>= 118 °C / 244 °F
31 °C / 88 °F

Evaporation rate

Flammability (solid, gas)

Flammability Limit in Air

No information available
No information available

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Specific Gravity 1.17

Water solubility No information available

\_\_\_\_\_

Solubility in other solvents No information available No information available **Partition coefficient** No information available **Autoignition temperature Decomposition temperature** No information available No information available Kinematic viscosity Dynamic viscosity No information available **Explosive properties** No information available No information available **Oxidizing properties** 

# **Other Information**

Softening point
Molecular weight
VOC Content (%)
No information available
No information available

**Density** 9.77 lbs/gal

Bulk density No information available

Percent solids by weight 71.2% Percent volatile by weight 28.8% Percent solids by volume 61.0% Actual VOC (lbs/gal) 2.8 Actual VOC (grams/liter) 337.7 EPA VOC (lbs/gal) 2.8 EPA VOC (grams/liter) 337.7 EPA VOC (lb/gal solids) 4.6

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

# **Possibility of Hazardous Reactions**

None under normal processing.

#### Conditions to avoid

Extremes of temperature and direct sunlight.

#### Incompatible materials

None known based on information supplied.

# **Hazardous Decomposition Products**

None known based on information supplied.

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Product Information No data available

**Inhalation** No data available.

**Eye contact** No data available.

**Skin Contact** No data available.

**Ingestion** No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Butyl Acetate	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
123-86-4			, ,

\_\_\_\_

Silica, Amorphous fumed 7631-86-9	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat)1 h
Methyl Amyl Ketone 110-43-0	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12.6 mL/kg(Rabbit)= 12600 μL/kg(Rabbit)	> 2000 ppm (Rat)4 h
Crystalline Silica 14808-60-7	= 500 mg/kg(Rat)	-	-
Aromatic 100 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	= 3400 ppm (Rat) 4 h
Mineral Spirits 64742-48-9	> 5000 mg/kg (Rat)	> 3160 mg/kg ( Rabbit )	-

#### Information on toxicological effects

**Symptoms** No information available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Chemical Name	ACGIH	IARC	NTP	OSHA
Silica, Amorphous fumed 7631-86-9	-	Group 3	-	-
Crystalline Silica 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Target Organ Effects Central nervous system, Eyes, lungs, Peripheral Nervous System (PNS), Respiratory

system, Skin.

Aspiration hazard No information available.

#### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

6.24% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Butyl Acetate 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
Silica, Amorphous fumed	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L	7600: 48 h Ceriodaphnia dubia
7631-86-9		LC50 static	mg/L EC50
Methyl Amyl Ketone 110-43-0	-	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	-
Aromatic 100	-	9.22: 96 h Oncorhynchus mykiss	6.14: 48 h Daphnia magna mg/L
64742-95-6		mg/L LC50	EC50
Mineral Spirits	-	2200: 96 h Pimephales promelas	2.6: 96 h Chaetogammarus marinus
64742-48-9		mg/L LC50	mg/L LC50

# Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Butyl Acetate 123-86-4	1.81
Methyl Amyl Ketone 110-43-0	1.98

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

US EPA Waste Number D001 U055 U239

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Butyl Acetate 123-86-4	Toxic

# 14. TRANSPORT INFORMATION

DOT

UN/ID no. UN1263
Proper shipping name Paint

Hazard Class Class 3, Flammable Liquid

Packing Group III

Special Provisions B1, B52, IB3, T2, TP1, TP29

**Description** UN1263, Paint, Class 3, Flammable Liquid, III

Emergency Response Guide 128

Number

**TDG** 

UN/ID no. UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group III

**Description** UN1263, Paint, 3, III

MEX

UN/ID no. UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group III

**Description** UN1263, Paint, 3, III

ICAO (air)

\_\_\_\_\_

UN/ID no. UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group III
Special Provisions A3, A72

**Description** UN1263, Paint, 3, III

IATA

UN/ID no. UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group III
ERG Code 3L
Special Provisions A3, A72

**Description** UN1263, Paint, 3, III

<u>IMDG</u>

UN/ID no. UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group III
EmS-No. F-E, S-E
Special Provisions 163, 223, 955
Description UN1263, Paint, 3, III

<u>RID</u>

UN/ID no. UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group III
Classification code F1

**Description** UN1263, Paint, 3, III

<u>ADR</u>

UN/ID no. UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group III
Classification code F1
Tunnel restriction code (D/E)

Special Provisions 163, 640E, 650

**Description** UN1263, Paint, 3, III, (D/E)

Labels 3

<u>ADN</u>

Proper shipping namePaintHazard Class3Packing GroupIIIClassification codeF1

Special Provisions 163, 640E, 650 Description UN1263, Paint, 3, III

Hazard label(s)3Limited quantity (LQ)5 LVentilationVE01

# 15. REGULATORY INFORMATION

**International Inventories** 

TSCA Complies

DSL/NDSL Complies \*

EINECS/ELINCS Complies \*

ENCS Does not comply \*

IECSC Complies \*

KECL Complies \*
PICCS Complies \*
AICS Complies \*

# Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute health hazardNoChronic Health HazardNoFire hazardYesSudden release of pressure hazardNoReactive HazardNo

### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Nan	ne (	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl Acetate 123-86-4		5000 lb	-	-	Х

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Butyl Acetate	5000 lb	-	RQ 5000 lb final RQ
123-86-4			RQ 2270 kg final RQ

# **US State Regulations**

# **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
Crystalline Silica - 14808-60-7	Carcinogen	
Cumene - 98-82-8	Carcinogen	

#### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Butyl Acetate 123-86-4	Х	X	X
Silica, Amorphous fumed 7631-86-9	Х	X	X
Methyl Amyl Ketone 110-43-0	X	X	Х
Crystalline Silica 14808-60-7	Х	X	X

<sup>\*</sup> This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

2,4 Pentane Dione 123-54-6	X	X	Х
Xylene 1330-20-7	X	X	X
Ethylene Glycol Butyl Ether 111-76-2	X	X	X
Propylene Glycol 57-55-6	X	-	X

# U.S. EPA Label Information

**EPA Pesticide Registration Number** Not applicable

# Hazardous air pollutants (HAPS) content

This product contains no reportable Hazardous Air Pollutants

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0 Physical and Chemical Properties -

HMIS Health hazards 2 \* Flammability 3 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend \*= Chronic Health Hazard

Revision Date 20-May-2015

**Revision Note** 

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

**End of Safety Data Sheet**