



# SAFETY DATA SHEET

Revision Date 12-May-2015

Version 2

## 1. IDENTIFICATION

**Product identifier**

**Product Name** Pool-Cote CR White Pool Paint

**Other means of identification**

**Product Code** LH-1410

**UN/ID no.** UN1263

**SKU(s)** None

**Recommended use of the chemical and restrictions on use**

**Recommended Use** No information available.

**Uses advised against** No information available

**Details of the supplier of the safety data sheet**

**Manufacturer Address**

Diamond Vogel Paint  
1020 Albany Place SE  
Orange City, IA 51041  
Phone: 712-737-4993  
Fax: 712-737-4997

**Emergency telephone number**

**Emergency Telephone** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

**Classification**

**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 2

### Emergency Overview

**Danger**

**Hazard statements**

May cause cancer  
Causes damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Highly flammable liquid and vapor

**Appearance** No information available**Physical state** liquid**Odor** No information available**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other Information**

• Toxic to aquatic life with long lasting effects  
 Unknown acute toxicity 32.41% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Tert-Butyl Acetate	540-88-5	10 - 30	*
Talc (powder)	14807-96-6	10 - 30	*
Titanium dioxide	13463-67-7	10 - 30	*
Solvent Naphtha, Medium Aliphatic	64742-88-7	5 - 10	*
Aromatic 150	64742-94-5	3 - 7	*
Crystalline Silica	14808-60-7	3 - 7	*
Zinc oxide, as Zn (fume)	1314-13-2	1 - 5	*
Chlorinated paraffin waxes	63449-39-8	1 - 5	*
Naphthalene	91-20-3	0.1 - 1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin Contact</b>	Consult a physician if necessary. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
<b>Inhalation</b>	Remove to fresh air. Call a physician. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a physician.
<b>Self-protection of the first aider</b>	Use personal protective equipment as required.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** No information available.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** CAUTION: Use of water spray when fighting fire may be inefficient.

**Specific hazards arising from the chemical**

Flammable.

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use personal protective equipment as required. Remove all sources of ignition.

**Environmental precautions**

**Environmental precautions** Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers. Cover liquid spill with sand, earth or other non-combustible absorbent material. Cover powder spill with plastic sheet or tarp to minimize spreading. Soak up with inert absorbent material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** None known based on information supplied.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Tert-Butyl Acetate 540-88-5	TWA: 200 ppm	TWA: 200 ppm TWA: 950 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 950 mg/m <sup>3</sup>	IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m <sup>3</sup>
Talc (powder) 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Crystalline Silica 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	(vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA total dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust
Zinc oxide, as Zn (fume) 1314-13-2	STEL: 10 mg/m <sup>3</sup> respirable fraction TWA: 2 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> fume TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 5 mg/m <sup>3</sup> fume (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) STEL: 10 mg/m <sup>3</sup> fume	IDLH: 500 mg/m <sup>3</sup> Ceiling: 15 mg/m <sup>3</sup> dust TWA: 5 mg/m <sup>3</sup> dust and fume STEL: 10 mg/m <sup>3</sup> fume
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m <sup>3</sup> (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m <sup>3</sup>	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> STEL: 15 ppm STEL: 75 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls**                      Showers  
 Eyewash stations  
 Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**                      Tight sealing safety goggles.

**Skin and body protection**                No special technical protective measures are necessary.

**Respiratory protection**                    If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations**        When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	No information available
<b>Appearance</b>	No information available	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks • Method</u></b>
<b>pH</b>	No information available	
<b>Melting point/freezing point</b>	No information available	
<b>Boiling point / boiling range</b>	>= 98 °C / 208 °F	
<b>Flash point</b>	4 °C / 40 °F	
<b>Evaporation rate</b>	No information available	
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	No information available	
<b>Lower flammability limit:</b>	No information available	
<b>Vapor pressure</b>	No information available	
<b>Vapor density</b>	No information available	
<b>Specific Gravity</b>	1.41	
<b>Water solubility</b>	No information available	
<b>Solubility in other solvents</b>	No information available	
<b>Partition coefficient</b>	No information available	
<b>Autoignition temperature</b>	No information available	
<b>Decomposition temperature</b>	No information available	
<b>Kinematic viscosity</b>	No information available	
<b>Dynamic viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Density</b>	11.72 lbs/gal
<b>Bulk density</b>	No information available
<b>Percent solids by weight</b>	63.0%
<b>Percent volatile by weight</b>	15.6%
<b>Percent solids by volume</b>	38.7%
<b>Actual VOC (lbs/gal)</b>	1.8

Actual VOC (grams/liter)	218.6
EPA VOC (lbs/gal)	2.8
EPA VOC (grams/liter)	336.3
EPA VOC (lb/gal solids)	4.7

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to avoid

Extremes of temperature and direct sunlight.

### Incompatible materials

None known based on information supplied.

### Hazardous Decomposition Products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	No data available
<b>Inhalation</b>	No data available.
<b>Eye contact</b>	No data available.
<b>Skin Contact</b>	No data available.
<b>Ingestion</b>	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Tert-Butyl Acetate 540-88-5	= 4100 mg/kg ( Rat )	> 2 g/kg ( Rabbit )	> 2230 mg/m <sup>3</sup> ( Rat ) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 5000 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h
Aromatic 150 64742-94-5	> 5000 mg/kg ( Rat )	> 2 mL/kg ( Rabbit )	> 590 mg/m <sup>3</sup> ( Rat ) 4 h
Crystalline Silica 14808-60-7	= 500 mg/kg ( Rat )	-	-
Zinc oxide, as Zn (fume) 1314-13-2	> 5000 mg/kg ( Rat )	-	-
Chlorinated paraffin waxes 63449-39-8	= 26100 mg/kg ( Rat ) > 21500 μL/kg ( Rat )	> 10 mL/kg ( Rabbit )	-
Naphthalene 91-20-3	= 1110 mg/kg ( Rat ) = 490 mg/kg Rat )	(= 1120 mg/kg ( Rabbit ) > 20 g/kg ( Rabbit )	> 340 mg/m <sup>3</sup> ( Rat ) 1 h

### Information on toxicological effects

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** No information available.

Chemical Name	ACGIH	IARC	NTP	OSHA
Talc (powder) 14807-96-6	-	Group 3	-	-
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Crystalline Silica 14808-60-7	A2	Group 1	Known	X
Chlorinated paraffin waxes 63449-39-8	-	Group 2B	-	X
Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	X

ACGIH (American Conference of Governmental Industrial Hygienists)  
 A2 - Suspected Human Carcinogen  
 A3 - Animal Carcinogen  
 IARC (International Agency for Research on Cancer)  
 Group 1 - Carcinogenic to Humans  
 Group 2B - Possibly Carcinogenic to Humans  
 Group 3 - Not classifiable as a human carcinogen  
 NTP (National Toxicology Program)  
 Known - Known Carcinogen  
 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
 X - Present

**Reproductive toxicity** No information available.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Target Organ Effects** Central nervous system, Central Vascular System (CVS), Eyes, lungs, Respiratory system, Skin.  
**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

35.28% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Tert-Butyl Acetate 540-88-5	-	296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	-
Talc (powder) 14807-96-6	-	100: 96 h Brachydanio rerio g/L LC50 semi-static	-
Solvent Naphtha, Medium Aliphatic 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	100: 48 h Daphnia magna mg/L EC50
Aromatic 150 64742-94-5	2.5: 72 h Skeletonema costatum mg/L EC50	19: 96 h Pimephales promelas mg/L LC50 static 2.34: 96 h Oncorhynchus mykiss mg/L LC50 1740: 96 h Lepomis macrochirus mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through 41: 96 h Pimephales promelas mg/L LC50	0.95: 48 h Daphnia magna mg/L EC50

Chlorinated paraffin waxes 63449-39-8	-	300: 96 h Lepomis macrochirus mg/L LC50 static 0.0109: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 94.5 - 271: 96 h Oncorhynchus mykiss mg/L LC50 static 0.1: 96 h Lepomis macrochirus mg/L LC50 flow-through	102: 24 h Daphnia magna mg/L EC50
Naphthalene 91-20-3	0.4: 72 h Skeletonema costatum mg/L EC50	5.74 - 6.44: 96 h Pimephales promelas mg/L LC50 flow-through 1.6: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.91 - 2.82: 96 h Oncorhynchus mykiss mg/L LC50 static 1.99: 96 h Pimephales promelas mg/L LC50 static 31.0265: 96 h Lepomis macrochirus mg/L LC50 static	2.16: 48 h Daphnia magna mg/L LC50 1.96: 48 h Daphnia magna mg/L EC50 Flow through 1.09 - 3.4: 48 h Daphnia magna mg/L EC50 Static

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Tert-Butyl Acetate 540-88-5	1.38
Aromatic 150 64742-94-5	2.9 - 6.1
Chlorinated paraffin waxes 63449-39-8	>6
Naphthalene 91-20-3	3.3

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001 U165

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Naphthalene 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145	-	U165

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes



Naphthalene 91-20-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-
------------------------	---	---	--	---

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Zinc oxide, as Zn (fume) 1314-13-2	Toxic
Naphthalene 91-20-3	Toxic

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no. UN1263  
 Proper shipping name Paint  
 Hazard Class Class 3, Flammable Liquid  
  
 Packing Group II  
 Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28  
 Description UN1263, Paint, Class 3, Flammable Liquid, II  
 Emergency Response Guide Number 128

**TDG**

UN/ID no. UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Description UN1263, Paint, 3, II

**MEX**

UN/ID no. UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Description UN1263, Paint, 3, II

**ICAO (air)**

UN/ID no. UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Special Provisions A3, A72  
 Description UN1263, Paint, 3, II

**IATA**

UN/ID no. UN1263

Proper shipping name	Paint
Hazard Class	3
Packing Group	II
ERG Code	3L
Special Provisions	A3, A72
Description	UN1263, Paint, 3, II

**IMDG**

UN/ID no.	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
EmS-No.	F-E, S-E
Special Provisions	163
Description	UN1263, Paint, 3, II

**RID**

UN/ID no.	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Classification code	F1
Description	UN1263, Paint, 3, II

**ADR**

UN/ID no.	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Classification code	F1
Tunnel restriction code	(D/E)
Special Provisions	163, 640C, 650
Description	UN1263, Paint, 3, II, (D/E)
Labels	3

**ADN**

Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Classification code	F1
Special Provisions	163, 640C, 650
Description	UN1263, Paint, 3, II
Hazard label(s)	3
Limited quantity (LQ)	5 L
Ventilation	VE01

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

TSCA	Complies
DSL/NDSL	Complies *
EINECS/ELINCS	Does not comply *
ENCS	Does not comply *
IECSC	Complies *
KECL	Does not comply *
PICCS	Does not comply *
AICS	Complies *

\* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

**Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

## US Federal Regulations

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Zinc oxide, as Zn (fume) - 1314-13-2	1.0
Naphthalene - 91-20-3	0.1

### **SARA 311/312 Hazard Categories**

<b>Acute health hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Tert-Butyl Acetate 540-88-5	-	-	-	X
Zinc oxide, as Zn (fume) 1314-13-2	-	X	-	-
Naphthalene 91-20-3	100 lb	X	X	X

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Tert-Butyl Acetate 540-88-5	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Naphthalene 91-20-3	100 lb 1 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

## US State Regulations

### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen
Chlorinated paraffin waxes - 63449-39-8	Carcinogen
Naphthalene - 91-20-3	Carcinogen
Lead Oxide - 1317-36-8	Carcinogen Developmental

### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Tert-Butyl Acetate 540-88-5	X	X	X

