



# SAFETY DATA SHEET

Revision Date 18-May-2015

Version 1

## 1. IDENTIFICATION

### Product identifier

**Product Name** Aisle Ease Gloss White Safety Marking

### Other means of identification

**Product Code** MC-1609

**SKU(s)** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** No information available.

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Diamond Vogel Paint  
1020 Albany Place SE  
Orange City, IA 51041  
Phone: 712-737-4993  
Fax: 712-737-4997

### Emergency telephone number

**Emergency Telephone** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity

Category 1A

### **Emergency Overview**

#### **Danger**

#### **Hazard statements**

May cause cancer



**Appearance** No information available

**Physical state** liquid

**Odor** No information available

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other Information**

• Causes mild skin irritation

Unknown acute toxicity

3.77% of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No.	Weight-%	Trade Secret
Titanium dioxide	13463-67-7	7 - 13	*
Kaolin	1332-58-7	1 - 5	*
Ethylene Glycol Butyl Ether	111-76-2	1 - 5	*
Ethanol	64-17-5	1 - 5	*
Ammonium Hydroxide	1336-21-6	0.1 - 1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****Description of first aid measures****General advice**

If symptoms persist, call a physician.

**Eye contact**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

**Skin Contact**

Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**Inhalation**

Immediate medical attention is not required. If symptoms persist, call a physician. Move to fresh air in case of accidental inhalation of vapors or decomposition products.

**Ingestion**

Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician. Do NOT induce vomiting.

**Self-protection of the first aider**

Use personal protective equipment as required.

**Most important symptoms and effects, both acute and delayed****Symptoms**

No information available.

**Indication of any immediate medical attention and special treatment needed****Note to physicians**

Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**Use. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray (fog). Alcohol resistant foam.

**Unsuitable extinguishing media** CAUTION: Use of water spray when fighting fire may be inefficient.

**Specific hazards arising from the chemical**

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions**

Use personal protective equipment as required. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges.

**Environmental precautions**

**Environmental precautions**

Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment**

Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up**

Dam up. Use personal protective equipment as required. Cover liquid spill with sand, earth or other non-combustible absorbent material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling**

Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions**

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in properly labeled containers.

**Incompatible materials**

None known based on information supplied.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH

Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Kaolin 1332-58-7	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Ethylene Glycol Butyl Ether 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m <sup>3</sup>
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Tight sealing safety goggles.

**Skin and body protection** No special technical protective measures are necessary.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations** When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	No information available
<b>Appearance</b>	No information available	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	9.7	
<b>Melting point/freezing point</b>	No information available	
<b>Boiling point / boiling range</b>	>= 64 °C / 147 °F	
<b>Flash point</b>	> 94 °C / > 201 °F	
<b>Evaporation rate</b>	No information available	
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	No information available	
<b>Lower flammability limit:</b>	No information available	
<b>Vapor pressure</b>	No information available	
<b>Vapor density</b>	No information available	
<b>Specific Gravity</b>	1.17	

<b>Water solubility</b>	No information available
<b>Solubility in other solvents</b>	No information available
<b>Partition coefficient</b>	No information available
<b>Autoignition temperature</b>	No information available
<b>Decomposition temperature</b>	No information available
<b>Kinematic viscosity</b>	No information available
<b>Dynamic viscosity</b>	No information available
<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Density</b>	9.77 lbs/gal
<b>Bulk density</b>	No information available
<b>Percent solids by weight</b>	48.4%
<b>Percent volatile by weight</b>	5.7%
<b>Percent solids by volume</b>	38.4%
<b>Actual VOC (lbs/gal)</b>	0.6
<b>Actual VOC (grams/liter)</b>	66.8
<b>EPA VOC (lbs/gal)</b>	1.2
<b>EPA VOC (grams/liter)</b>	144.6
<b>EPA VOC (lb/gal solids)</b>	1.5

<b>10. STABILITY AND REACTIVITY</b>
-------------------------------------

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

None known based on information supplied.

**Hazardous Decomposition Products**

None known based on information supplied.

<b>11. TOXICOLOGICAL INFORMATION</b>
--------------------------------------

**Information on likely routes of exposure**

<b>Product Information</b>	No data available
<b>Inhalation</b>	No data available.
<b>Eye contact</b>	No data available.
<b>Skin Contact</b>	No data available.
<b>Ingestion</b>	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
---------------	-----------	-------------	-----------------

Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Ethylene Glycol Butyl Ether 111-76-2	= 470 mg/kg ( Rat )	= 99 mg/kg ( Rabbit )	= 450 ppm ( Rat ) 4 h
Ethanol 64-17-5	= 7060 mg/kg ( Rat )	-	= 124.7 mg/L ( Rat ) 4 h
Ammonium Hydroxide 1336-21-6	= 350 mg/kg ( Rat )	-	-

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Ethylene Glycol Butyl Ether 111-76-2	A3	Group 3	-	-
Ethanol 64-17-5	A3	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)  
 A3 - Animal Carcinogen  
 IARC (International Agency for Research on Cancer)  
 Group 1 - Carcinogenic to Humans  
 Group 2B - Possibly Carcinogenic to Humans  
 Group 3 - Not classifiable as a human carcinogen  
 NTP (National Toxicology Program)  
 Known - Known Carcinogen  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
 X - Present

**Reproductive toxicity** No information available.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Chronic toxicity** Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Contains a known or suspected reproductive toxin.  
**Target Organ Effects** blood, Central nervous system, Eyes, Hematopoietic System, kidney, liver, lungs, Reproductive System, Respiratory system, Skin.  
**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

16.4% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Ethylene Glycol Butyl Ether 111-76-2	-	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	1000: 48 h Daphnia magna mg/L EC50 1698 - 1940: 24 h Daphnia magna mg/L EC50

Ethanol 64-17-5	-	12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	9268 - 14221: 48 h Daphnia magna mg/L LC50 2: 48 h Daphnia magna mg/L EC50 Static 10800: 24 h Daphnia magna mg/L EC50
Ammonium Hydroxide 1336-21-6	-	8.2: 96 h Pimephales promelas mg/L LC50	0.66: 48 h water flea mg/L EC50 0.66: 48 h Daphnia pulex mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Ethylene Glycol Butyl Ether 111-76-2	0.81
Ethanol 64-17-5	-0.32

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging**

Do not reuse container.

**US EPA Waste Number**

U112 U122 U154

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Ethanol 64-17-5	Toxic Ignitable
Ammonium Hydroxide 1336-21-6	Toxic Corrosive

**14. TRANSPORT INFORMATION****DOT**

Not regulated

**15. REGULATORY INFORMATION****International Inventories**

TSCA	Complies
DSL/NDSL	Complies *
EINECS/ELINCS	Does not comply *

ENCS	Does not comply *
IECSC	Complies *
KECL	Complies *
PICCS	Complies *
AICS	Complies *

\* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

### US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Ethylene Glycol Butyl Ether - 111-76-2	1.0

#### SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ammonium Hydroxide 1336-21-6	1000 lb	-	-	X

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ammonium Hydroxide 1336-21-6	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

### US State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethanol - 64-17-5	Carcinogen Developmental
Methanol - 67-56-1	Developmental
Formaldehyde - 50-00-0	Carcinogen

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
---------------	------------	---------------	--------------



Titanium dioxide 13463-67-7	X	X	X
Ethylene Glycol Butyl Ether 111-76-2	X	X	X
Kaolin 1332-58-7	X	X	X
Ethanol 64-17-5	X	X	X
Ammonium Hydroxide 1336-21-6	X	X	X
Ethyl Acetate 141-78-6	X	X	X
Ammonia (anhydrous) 7664-41-7	X	X	X
Formaldehyde 50-00-0	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**Hazardous air pollutants (HAPS) content**

This product contains no reportable Hazardous Air Pollutants

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	Health hazards 2	Flammability 1	Instability 0	Physical and Chemical Properties -
<b>HMIS</b>	Health hazards 2 *	Flammability 1	Physical hazards 0	Personal protection X

*Chronic Hazard Star Legend*

\* = Chronic Health Hazard

**Revision Date**

18-May-2015

**Revision Note**

No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

**End of Safety Data Sheet**